SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Livingston 2000 NOV 15 A 9:29 Located In: Corner Code ≠≠ (County) NANCY HAVILAND REGISTER OF DEEDS LIVINGSTON COUNTY, MI. T 4N R 6E J-5 Public Land Survey _____ R _____ Т 48843 T____R____ T ____ R __ Property Controlling 2. S _____ T _____ R _____ LSC #1358m S ____ T ___ R ____ S ____ T ___ R ____ in Section Miscellaneous 0 3 **Register of Deeds Stamp & File Number** Property in Sec. S_____R 4. Lot No. ____, Recorded Plat ____ Private Claims ___ 5 Ed Anderson . in a field survey on_ 10-18 2000 . 19

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

	A	в	с	D	E	F	G	н	1.	ĸ	L	ĸ
2		6		5—		4_		3		2		
3		 				L						
4		ļ		 	L!	 9—	L	0	1	,	1	2
5	 	_	 		_	 						
6	L	 18—-	<u> </u> ₁	ا ۲	L-1		1	5	1	4	1	з—
7	_	4	ļ			L					_	
8	L	 19	-2	0		h		2	2	3	2	4
9					_	ļ					_	
10	ļ;	 30	2	 9—	_2	 8	2	7—-	2	6	2	5
11	-	_	 									-i
12	-;		-3	2	3	3	3	4	3	5—	3	6
13		L					l					

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-5 Found 1/2" Rod in Concrete Monument

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: J-5 South 1/4 corner Section 11, T4N-R6E

Set Brass Cap (Liv. Co. Mon. Cor.) on Rod in Concrete Monument N 05° E, 19.01' Set Nail and Liv. Co. Remon Tag in West face 14" Oak N 30° W, 32.99' Set Nail and Liv. Co. Remon Tag in West face 18" Oak N 75° W, 33.69' Set Nail and Liv. Co. Remon Tag in North face 26" Oak S 15° E, 25.54' Set Nail and Liv. Co. Remon Tag in East face 20" Cherry



Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 23, 1971 Revised May 14, 1973 Revised Jan., 1983

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

FILED