

SURVEY &
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in
Livingston
(County)

Located In:

Corner Code #

2000 NOV 15 A 9:29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

1. Public Land Survey

T 4N R 6E

K-8

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

LSC #1361m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Ed Anderson, in a field survey on 10-18, 19 2000,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-8 Found 1/2" Iron

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 6-21-00 CO. REP JED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-8 West 1/4 corner Section 24, T4N-R6E

Set 1 1/4" x 36" Iron Pipe w/Brass Cap (Liv. Co. Mon. Cor.)

N 25° W, 77.49' Set Nail and Liv. Co. Remon Tag in Southwest face Power Pole

S 35° W, 49.41' Set Nail and Liv. Co. Remon Tag in East face 16" Elm

S 55° E, 50.05' Set Nail and Liv. Co. Remon Tag in North face Triple Boxelder

East, 45.18' Set Nail and Liv. Co. Remon Tag in South face 30" Boxelder

Signed by

Date

Surveyor's Michigan License No.

