## MACKINAC COUNTY REMONUMENTATION CORNER

## LAND CORNER RECORDATION CERTIFICATE

For corners in	Filing Requi	rement of Act 74, I	Mich. <b>P.A</b> . 1970
Mackinac	Located In:	Corner Code =	#
1. Public Land Survey	T40N R04W T R	P.C.C. 16 NW Cor. PC	RECEIVED & FILED  DIAME PRODUCE ROLLING  DEC 1 1 1995
<ol> <li>Property Controlling in Section</li> <li>Miscellaneous Property in Sec.</li> </ol>	T R S T R S T R S T R	#21	AM PM 7[8[5]
I. Neil E. Hill  do hereby certify that under red in lines 1 and 2 above were in current manual of survey instr Management or by a decree of above were in conformance with Court of Law; established, expressed below:  NOTE: Not more than 4 con this certificate.	monument and accessories at 2W 10 lks 8E 11 lks.	EMBER 17 A of 1970, the corner po and rules therefore as rartment of the Interior, Ener points mentioned in d of Land Surveyors or be-monumented, recover and range, may be re-	2
•	evidence found and/or method d at prorated distance on V		or reestablishing corner:
	b #27447. Replaced with E 42.99' E 25.20' W 30.30	SURVIEW PROFILE OF IOSO A HELDON Sestablished to perpose 5/8" re-rod std. con S51-03-40E	NEIL E. HILL Land Surveyor No. 27447 TAMEETING Hetuate locating the position of the corner: mty remonumentation corner. 467.01 feet to SW Cor. PC 16 967.33 feet to NW Cor. PC 17

Signed by

Surveyor's Michigan License No. \_\_\_\_\_27447\_\_\_\_\_

Neil E Mill VS \_\_ Date FORM APPROVED BY NICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 Revised May 14, 1975 Revised Jan., 1983

NOVEMBER 17, 1905