

SURVEY & REMONUMENTATION

MAR 13 1998

MACKINAC COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

Mackinac  
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 41N R 3W #5 WCMC A-7/A-8 ✓  
T R Section 19

Also recorded as

T 41N R 4W #5 WCMC M-7/M-8  
T R Sections 24

2. Property Controlling  
in Section

S T R  
S T R

3. Miscellaneous  
Property in Sec.

S T R  
S T R

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED & FILED  
DIANE FRANKOVICH  
MACKINAC COUNTY CLERK OF DEEDS

DEC 29 1997

AM PM  
7/8/9/10/11/12/13/14/15/16

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

I, Neil E. Hill, in a field survey on DECEMBER 22, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1840 GLO notes William Burt 5" W. Birch Meander Corner  
1984 James Granger set 1/2" re-rod with cap #16041  
Recorded Liber C, page 75

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1997 Found re-rod with cap. 3' from water  
DNR sign post N45W 66.92 feet  
8" Cedar S55W 75.42 feet  
12" Bent cedar S22E 105.22 feet  
10" Spruce S55E 36.43 feet

Recorded as 2319.90' from 1/4 Corner to South

Moved corner away from water's edge.


ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER P.A.  
345 OF 1990 AT A MEETING  
HELD ON 12-12-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1/2" re-rod and remonumentation cap 48' from shore of Lake Huron.

Re-set at 2275.00' from 1/4 Corner.

8" W. Birch S35E 41.58'  
8" Cedar S70E 23.27'  
8" Bent Cedar N70E 29.02'  
8" Cedar N80W 60.90'



Signed by Neil E. Hill P.S.  
Surveyor's Michigan License No. 27447

Date DECEMBER 22, 1997