

SURVEY & REMONUMENTATION

146

MAR 13 1998

MACKINAC COUNTY REMONUMENTATION CORNER

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 40N R 3W (#1) WCMC A1/B1

T R Section 6

T 41N R 3W (#6) WCMC A13/B13

T R Section 31

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REC'D & FILED
DEC 29 1997
PM
7181010111213141516

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Neil E. Hill

DECEMBER 22 97

I, in a field survey on , 19 , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1840 GLO notes William Burt 9" Tamarack N58½W 72 links
4" Fir S84W 27 links

Line for corner is shown on the Plat of Evergreen Shores

No records of corner being perpetuated.

GLO distance 805.20

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1997 Found P.K. nail set on the E-W Section Line and the Easterly ROW line of Bus I-75. Checked position, set monument box & rod with re-monumentation cap.

Corner set at 631.91' from Section corner.

Plat concrete monument is at 887.62' from Section corner.


ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 12-12-97

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found PK at intersection of E-W Section Line and Easterly ROW line of Bus I-75. Set rod & cap and monument box.

Utility pole S45E 37.20' NW Brick Cor Building N30E 54.96'

Utility Pole N15W 88.84' 20" Spruce N15E 71.26'



Signed by Neil E. Hill P.S.

Date

DECEMBER 22, 1997

Surveyor's Michigan License No. 27447