

OCT 1 1 1994

## COMMISSION

## MACKINAC COUNTY REMONUMENTATION CORNER LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1848  12° Birch N69E 0.17 ch 11° Bugar Maple N35W 0.11 ch  Additional Mullet 1845  12° Sugar Maple S35W 0.40 ch 6° Sugar Maple S65E 0.20 ch  B. Description of corner evidence found and/or method applied in restoring or recstablishing corner:  1981 Stockholm duy and recovered pipe and rock 2' below surface; recorded Liber B, Page 384  1994 Found 3" brass tablet 1 foot below gravel road surface P, Pole N62E 36.8'  5° Cedar N53W 35.7'  4° Cedar S78E 48.9'  Narker post N28W 49.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  3° P, Pole N62E 36.9'  5° Cedar N53W 35.7'  4° Cedar S78E 48.9'  Narker post N28W 48.6'  Date N62E 36.9'  110	For corners in	i initg riequii	ement of Act 14, Intell. 1.2	a. 1970
1. Public Land Survey  T. 40N R. 4N  T. 51N R. 51N	Mackinac	t analog lav	0	
1. Public Land Survey  T. A.D. R. A. R	(County)	Located III.	Corner Code 74	RECEIVED & FILED
2. Property Controlling S T R R Residence of Stamp & File Number R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R Register of Deeds Stamp & File Number R R R R R R R R R R R R R R R R R R R				DIAME FRAT KOVICH
SEP 6 1994  AM PM  AM PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R PM  Tislible to the controlling S T R R R PM  Tislible to the controlling S T R R R R PM  Tislible to the controlling S T R R R R R PM  Tislible to the controlling S T R R R R R R R R R R R R R R R R R R	Public Land Survey			MAC
2. Property Controlling S   T   R			R-13 \\	2010
2. Property Controlling S T R T R T STORY CONTROL STATE STAT				
in Section S T R Property in Sec. S T R  4. Lot No Recorded Plat 5. Private Claims  Neil E Hill I in a lind survey on August 22 94  4. Lot No Recorded Plat 5. Private Claims  Neil E Hill I in a lind survey on August 22 94  4. Control and 2 Above were incommon of A Andrew Medical Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 1 in a lind survey on Control of Section 2 in a lind survey on Control of Sec	2 Proporty Controlling 9		A-1-4	1 1 1 4
3. Miscellaneous S T R R Register of Deeds Stamp & File Number Property in Sec. S T R R Register of Deeds Stamp & File Number Property in Sec. S T R R Register of Deeds Stamp & File Number Property in Sec. S T R R Register of Deeds Stamp & File Number Property in Sec. S T R R Register of Deeds Stamp & File Number Property in Sec. S T R R Register of Deeds Stamp & File Number Register of Deeds Stamp & File Number Register of Deeds Stamp & File Number Register of Deeds Register				4319 1 1 1 2 1 1 2 1 3 4 5 G
A Lot No				·
A Lot No			•	Register of Deeds Stamp & File Number
Neil E. Hill in a field survey on August 22 19 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	riopolity in opol	reconstruction of the company control of the contro		
Neil E. Hill in a field survey on August 22 19 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	4. Lot No, Record	ied Plat	<u> </u>	
Neil E. Hill is a field survey on August 22 94 10 horby-certify that under requirements of PA.74, Michagan PA. of 1872, the corresponds mentioned in the current remained of survey instructions of the United States Department of the Interior. Burnied in the current remained of survey instructions of the United States Department of the Interior, Burnau of Land Management of the Adaption and office and the Interior. Burnau of Land Management of the Adaption of States Department of the Interior, Burnau of Land Management of the Adaption of Land Management of the Adaption of Land Management of States Department of the Interior, Burnau of Land Management of States Department of the Interior, Burnau of Land Management of States Department of the Interior, Burnau of Land Management of States Department of Land Streyors or by a Decree of a court of Law devoluted Land Management of States Department of Land Management of				
Neil E. Hill is a field survey on August 22 94 10 horby-certify that under requirements of PA.74, Michagan PA. of 1872, the corresponds mentioned in the current remained of survey instructions of the United States Department of the Interior. Burnied in the current remained of survey instructions of the United States Department of the Interior, Burnau of Land Management of the Adaption and office and the Interior. Burnau of Land Management of the Adaption of States Department of the Interior, Burnau of Land Management of the Adaption of Land Management of the Adaption of Land Management of States Department of the Interior, Burnau of Land Management of States Department of the Interior, Burnau of Land Management of States Department of the Interior, Burnau of Land Management of States Department of Land Streyors or by a Decree of a court of Law devoluted Land Management of States Department of Land Management of				2 - 6 - 5 - 4 - 3 - 2 - 1
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on the certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1840  12" Surgar Haple N35W 6.11 ch  14" Sugar Haple N35W 6.11 ch  6" Sugar Maple S65E 9.28 ch  12" Surgar Maple S65E 9.28 ch  13" Surgar Maple S65E 9.28 ch  14" Cedar N55W 35.7"  4" Cedar				3
in a field survey on the first survey on the first survey on the first survey of the first survey on the first survey on the first survey on the first survey of the f	Neil E. Hill		August 22 94	4 - 7 - 8 - 9 - 10 - 11 - 12
in lines it and 2 above were in conformance with regulations and rules therefore as required in the current immated of survey instructions of the United States Department of the Interior, Browsou of Land Management of by a decree of a Court of Law and/or that the corner points meritored in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors of by a Decree of a Court of Law and/or that the corner points meritored in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors of by a Decree of a Court of Law and/or that the corner points meritored in lines 3, 4 and 5 above were in conformance with the rules of the Michigan License No.  ROTE: Not more than 4 corners, all in the same town and renge, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1848  12° Birch N67E 8.17 ch  11' Supar Maple N35W 0.11 ch  Additional Mullet 1845  12' Supar Maple S63E 8.20 ch  B. Description of corner evidence found and/or method applied in restoring or recetablishing corner:  1981 Stockhola duy and recovered pipe and rock 2' below surface; recorded Liber B, Page 394  1988 MDDT tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface  P. Pole N62E 36.9'  Scar N53W 35.7'  4" Cedar S78E 48.9'  Marker post N28W 49.6'  Sescription of monument for corner and accessories established to perpetuate localing the position of the corner:  Accepted the corner in its current location.  Accepted the corner in the lowest law in the lowest		field survey on	. 19	
Current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management of by decree at Count of Law decree in Count of				
Management of by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Law, established, re-established, monumented, re-onumented, recovered, found as expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1849  12° Birch N67E 8.17 ch 11° Supar Maple N35N 9.11 ch Additional Mullet 1945  12° Suyar Maple S45E 8.28 ch  B. Description of corner evidence found and/or method applied in restoring or recetablishing corner:  1981 Stockhola dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 394  1988 MD01 tied and used  1994 Found 3" brass tablet 1 font below gravel road surface P. Fole N62E 36.8'  5" Cedar N53W 35.7' 4" Cedar S78E 48.9' Marker post N28W 49.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accep		•	•	
Court of Lew: established, re-established, monumented, re-monumented, recovered, found as superseased below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1849  12" Birch N69E 8.17 ch 11" Sugar Naple N35W 0.11 ch  Additional Mullet 1845  12" Sugar Naple S36W 0.40 ch 6" Sugar Naple S36W 0.40 ch 6" Sugar Naple S36W 0.40 ch 6" Sugar Naple S36W 0.40 ch 5" Codar N53W 35.77  4" Cedar N53W 35.77  4" Cedar N53W 35.77  4" Cedar N28W 48.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the corner in its current location.  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  3" P. Pole N62E 36.9'  5" Cedar N53W 35.77'  4" Cedar N53W 35.77'  4				nd5
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Orignal set wood post by Burt 1840  12" Birch  18 Sugar Maple  12" Sureh  Additional Mullet 1845  12" Sugar Naple  16" Sugar Maple  16" Sugar Maple  16" Sugar Maple  1794 Stockholm dug and recovered pipe and rock 2" below surface; recorded Liber B, Page 384  1898 MDDT tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface  1995 P. Pole  1986 N62E 36.9"  1986 ACCEPTED BY THE MACKINAC COUNTY  1987 Survey PEER GROUP AS THE OFFICIAL CORNER UNDER PA  345 OF 1999 AT A MEETING  1980 HELDON 6-16-19  1980 ACCEPTED BY THE MACKINAC COUNTY  1980 Survey PEER GROUP AS THE OFFICIAL CORNER UNDER PA  345 OF 1999 AT A MEETING  1980 HELDON 6-16-19  1980 ACCEPTED BY THE MACKINAC COUNTY  1980 Survey PEER GROUP AS THE OFFICIAL CORNER UNDER PA  345 OF 1999 AT A MEETING  1981 HELDON 6-16-19  1982 ACCEPTED BY THE MACKINAC COUNTY  1982 ACCEPTED BY THE MACKINAC COUNTY  1983 Survey PEER GROUP AS THE OFFICIAL CORNER UNDER PA  345 OF 1999 AT A MEETING  1984 HELDON 6-16-19  1985 ACCEPTED BY THE MACKINAC COUNTY  1985 ACCEPTED BY THE MACKINAC COUNTY  1986 ACCEPTED BY THE MACKINAC COUNTY  2086 ACCE			• • • • • • • • • • • • • • • • • • • •	
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1848  12° Birch N69E 0.17 ch 11° Bugar Maple N35W 0.11 ch  Additional Mullet 1845  12° Sugar Maple S35W 0.40 ch 6° Sugar Maple S65E 0.20 ch  B. Description of corner evidence found and/or method applied in restoring or recstablishing corner:  1981 Stockholm duy and recovered pipe and rock 2' below surface; recorded Liber B, Page 384  1994 Found 3" brass tablet 1 foot below gravel road surface P, Pole N62E 36.8'  5° Cedar N53W 35.7'  4° Cedar S78E 48.9'  Narker post N28W 49.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  3° P, Pole N62E 36.9'  5° Cedar N53W 35.7'  4° Cedar S78E 48.9'  Narker post N28W 48.6'  Date N62E 36.9'  110		blished, monumented, re-	monumented, recovered, found	
on this certificate.  A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1849  12° Birch N69E 0.17 ch 11° Sugar Maple N35W 0.11 ch  Additional Multet 1945  12° Sugar Maple S30W 0.40 ch 6° Sugar Maple S65E 0.20 ch  B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  1981 Stockholm dup and recovered pipe and rock 2' below surface; recorded Liber B, Page 394  1988 NDDI tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface F. Pole N62E 36.9° 5" Cadar N53W 35.7' 4" Cedar S78E 48.9' Marker post N20W 49.6'  Bescription of monument for corner and accessories established to perpetuate locating the position of the corner:  OBescription of monument for corner and accessories established to perpetuate locating the position of the corner:  OBescription of monument for corner and accessories established to perpetuate locating the position of the corner:  NEIL E. HILL Land Surveyor Michigan License No.  27447  Date  August 22, 1994	·	- all in the same town -		
A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1840  12" Birch N69E 0.17 ch 11" Sugar Maple N35M 0.11 ch  Additional Mullet 1845  12" Sugar Maple S36W 0.40 ch 4" Sugar Maple S45E 9.20 ch  B. Description of corner evidence found and/or method applied in rectoring or reestablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 304  1998 MDOT tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface P. Pole N62E 36.0"  15" Cedar N53W 33.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the works witnesses as follows: P. Pole N62E 36.0"  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the WSFS witnesses as follows: P. Pole N62E 36.0"  Accepted the works witnesses as follows: P. Pole N62E 36.0"  Accepted the works witnesses as follows: P. Pole N62E 36.0"  Hell Milliam Market post N20W 48.6'  N60 August 22, 1994  Surveyor's Michigan License No. 27447		s, an in the same town a	nd range, may be recorded	
A. Description of original monument and accessories and/or subsequent restoration:  Original set wood post by Burt 1840  12° Barch 11° Sugar Maple NSSW 0.17 ch 11° Sugar Maple SSGW 0.49 ch 4° Sugar Maple SGSW 0.49 ch 4° Sugar	on and bermioate.			
Orignal set wood post by Burt 1849  12" Birch N69E 8.17 ch 11" Sugar Maple N35W 8.11 ch  Additional Mullet 1845  12" Sugar Maple S36W 8.40 ch 6" Sugar Maple S65E 8.29 ch  B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 384  1988 MDOT tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface	A. Description of original monu	ment and accessories an	d/or subsequent restoration:	
12" Birch NA9E 0.17 ch 11" Sugar Maple N35W 0.11 ch Additional Mullet 1845 12" Sugar Maple S38W 0.48 ch 6" Sugar Maple S65E 0.28 ch  8. Description of corner evidence found and/or method applied in restoring or recetablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 384 1988 MDDT tied and used 1994 Found 3" brass tablet 1 foot below gravel road surface P. Pole N62E 36.9' 5" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 48.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location. Accepted the USFS witnesses as follows: P. Pole N62E 36.8' Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the USFS witnesses as follows: P. Pole N62E 36.8' Scredar N53W 35.7' 4" Cedar S70E 48.7' Marker post N20W 40.6'  Surveyor's Michigan License No.  27447  Date  August 22, 1994	· -		• •	
11" Sugar Maple N35W 0.11 ch  Additional Mullet 1845  12" Sugar Maple S39W 0.49 ch  6" Sugar Maple S65E 9.28 ch  8. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 384  1988 MD0T tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface P, Pole N62E 36.8'  5" Cedar N53W 35.7'  4" Cedar S70E 48.9'  Marker post N28W 49.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows: P, Pole N62E 36.9'  5" Cedar N53W 35.7'  4" Cedar S70E 48.9'  Marker post N28W 48.6'  Surveyor's Michigan License No. 27447  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT MATHROUGH BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 23, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 24, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 24, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 24, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 24, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD OF LAND SURVEYES, JAM. 24, 47  POINT ATTROUTE BY MICHIGAN STRIFE BORD		•		
Additional Mullet 1945  12" Suyar Maple S38W 8.48 ch 6" Suyar Maple S65E 8.28 ch  8. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  1981 Stockholm duy and recovered pipe and rock 2' below surface; recorded Liber B, Page 384  1988 MD0T tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface P. Pole N62E 36.8"  5" Cedar N53W 35.7' 4" Cedar S78E 48.9' Marker post N28W 48.6'  ACCEPTED BY THE MACKINAC COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER INDER P.A. 345 OF 1980 AT A MEETING HELDON 8-16-19.  June H. Human State 100 A Meeting of the position of the corner:  Accepted the corner in its current location. Accepted the USFS witnesses as follows: P. Pole N62E 36.8' S" Cedar N33W 35.7' 4" Cedar S78E 48.9' Marker post N28W 48.6'  S" Cedar N33W 35.7' 4" Cedar S78E 48.9' Marker post N28W 48.6'  STOCK AND A MEETING HELL IN A MEDICAL COUNTY Marker post N28W 48.6'  STOCK AND A MEETING HELL IN A MEDICAL COUNTY SURVEY PEER GROUP AS THE COUNTY SURVEY PEER GROUP AS THE MACKINAC COUNTY SURVE				
12" Suyar Maple S30W 0.49 ch 6" Suyar Maple S65E 0.20 ch  8. Description of corner evidence found and/or method applied in restoring or recatablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 304  1988 MD0T tied and used  1998 Found 3" brass tablet 1 foot below gravel road surface P. Fole N62E 36.8'  5" Cedar N53W 35.7' 4" Cedar S70E 48.7'  Marker post N20W 40.6'  Bescription of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location. Accepted the corner in its current location. Accepted the USFS witnesses as follows:  D. Pole N32W 35.7' 4" Cedar N53W 35.7' 4" Cedar S70E 48.9' Narker post N20W 40.6'  Surveyor's Michigan License No. 274.47  PDIM AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 23, 8  POLINA AMPRIOUS BY MICHIGAN SIMILE 100AD BY LIMPS SURVEYORS, JAM. 24, 8		MOON GETT CI		
8. Description of corner evidence found and/or method applied in restoring or recetablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 304 1988 MDDT tied and used 1994 Found 3" brass tablet 1 foot below gravel road surface P, Pole NASE 36.0' S" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location. Accepted the USFS witnesses as follows: P, Pole NG2E 36.0' S" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Signed by  Date  August 22, 1994  Surveyor's Michigan License No. 27447		930H 0.40 et		
B. Description of corner evidence found and/or method applied in restoring or recatablishing corner:  1981 Stockholm dug and recovered pipe and rock 2' below surface; recorded Liber B, Page 384 1988 MDDT tied and used  1994 Found 3" brass tablet 1 foot below gravel road surface P. Pole N62E 36.0"  1986 ST. Cedar N53W 35.7'  4" Cedar S70E 48.9'  Narker post N20W 40.6'  Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows: P. Pole N62E 36.0'  3" Cedar N53W 35.7'  4" Cedar N53W 35.7'  4" Cedar S70E 48.9'  Mill Land  Marker post N20W 40.6'  Date August 22, 1994  Surveyor Michigan License No. 27447				
Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location. Accepted the USFS witnesses as follows:  P. Pole N62E 36.0'  Tredar N53W 35.7'  4" Cedar N50E 48.9' Marker post N20W 40.6'  Date  August 22, 1994  FORM APPROVED BY MICHIGAR STATE EBOARD OF LAND SURVEYORS, JAR. 28, 18.	1981 Stockholm dug an 1988 MDOT tied and us 1994 Found 3" brass t P. Pole 5" Cedar 4" Cedar	nd recovered pipe sed ablet 1 foot belo N62E 36.0' N53W 35.7' S70E 48.9'	and rock 2' below su w gravel road surfac	rface; recorded Liber B, Fage 304  e  ACCEPTED BY THE MACKINAC COUNTY
HELDON 6-16-94  James H. James			Ċ	OFFICIAL CORNER UNDER P.A.
Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  P. Pole N62E 36.8'  5" Cedar N53W 35.7'  4" Cedar S70E 48.9'  Marker post N20W 40.6'  Date  August 22, 1994  Surveyor's Michigan License No.  27447				
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  P. Pole N62E 36.0' 5" Cedar N53W 35.7' 4" Cedar S70E 48.9' Plarker post N20W 40.6'  Surveyor's Michigan License No.  Date  August 22, 1994  FORM APPROVED BY MICHIGAN STATE EDARD OF LAND SURVEYORS, JAN. 28, 18	O		r	
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  P. Pole N62E 36.0' 5" Cedar N53W 35.7' 4" Cedar S70E 48.9' Plarker post N20W 40.6'  Surveyor's Michigan License No.  Date  August 22, 1994  FORM APPROVED BY MICHIGAN STATE EDARD OF LAND SURVEYORS, JAN. 28, 18	100			James of Xrange
Accepted the corner in its current location.  Accepted the USFS witnesses as follows:  P. Pole N62E 36.0'  5" Cedar N53W 35.7'  4" Cedar S70E 48.9'  Marker post N20W 40.6'  Signed by  Date  August 22, 1994  Surveyor's Michigan License No.  27447  FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 18	Ļ			
Accepted the USFS witnesses as follows:  P. Pole N62E 36.0'  S" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Date  August 22, 1994  Surveyor's Michigan License No.  27447  FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAM, 28, 19	C. Description of monument for	corner and accessories e	established to perpetuate loca	ating the position of the corner:
Accepted the USFS witnesses as follows:  P. Pole N62E 36.0'  S" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Date  August 22, 1994  Surveyor's Michigan License No.  27447  FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAM, 28, 19	<sub>F</sub> A			
P. Pole N62E 36.0' 5" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Signed by			ion.	and a second
5" Cedar N53W 35.7' 4" Cedar S70E 48.9' Marker post N20W 40.6'  Signed by				OF MICHIGAN
4" Cedar S70E 49.9"  Marker post N20W 40.6"  Signed by				NEIL #
Marker post N20W 40.6°  No. 27447  Signed by Date August 22, 1994  Surveyor's Michigan License No 27447  FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19				
Signed by Date August 22, 1994 Surveyor's Michigan License No 27447 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26, 19			•	
Signed by Date August 22, 1994	neo ker post †>	INCOM HOND		Same and the same
Surveyor's Michigan License No. 27447	<b>出</b> 意			27447
Surveyor's Michigan License No. 27447	ૢૻૺૺૼૼૺૺ૾ૼ			THE THE STATE OF T
Surveyor's Michigan License No. 27447	Hi'			A THE TARREST
Surveyor's Michigan License No. 27447	~~ ·		<b>N</b> •	
Surveyor's Michigan License No. 27447	Signed by	E. Mill	7.5 Date	August 22 1994
FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAH. 28, 19	Survevor's Michigan License No.	C) 17 4 4 17		
09-06-94 1CL3183	o o	THE STATE OF THE S		DEVICED MAY 14 501