

JAN 21 1999

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Mackinac County Remonumentation Corner

For corners in

Mackinac County

Located in:

Corner Code #

1. Public Land Survey

T42N R01W

MC E-5/F-5

#1

T R

T R

T R

2. Property Controlling  
in Section

S S

T R

T R

3. Miscellaneous  
Property in Sec.

S S

T R

T R

4. Lot No., Recorded Plat

5. Private Claims

RECEIVED & FILED  
DIANE FRANKOVICH  
MACKINAC COUNTY REGISTER OF DEEDS

DEC 31 1998

AM PM  
7/8/9/10/11/12/1/2/3/4/5/6

Register of Deeds Stamp & File Number

I, Neil E Hill, in a field survey on 12-21-98, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845 GLO Notes James Mullett 12" Tamarack for post

1956 DNR Billy Buckler 9" Red Oak N 41 W 69 lks  
1" iron pipe w/ 4" brass cap 7" W Birch N 12 E 25 lks  
On West shore of Bay City Lake  
Liber 2, Page 304

ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER PA.  
345 OF 1990 AT A MEETING  
HELD ON 12-04-98 NEH

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1998 No evidence of corner found  
Corner set by Buckler was at 6 ch, GLO indicated 4.10 ch  
Set 1/2 re-rod at pro-rated GLO distance on-line between section and 1/4 corners

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is 1/2" re-rod with 4" Alum. remonumentation cap  
Corner is approx 125' from West shore of Bay City Lake

18" Oak N 25 W 28.00'  
18" Oak S 15 W 23.16'  
18" Oak S 85 W 14.18'  
5" W Pine S 65 E 28.01'

Bearings are compass bearings, corrected for declination, all distances are to a double-headed nail in the side of the witness object unless otherwise noted.

Signed by Neil E Hill P.S.

Date 12-29-98

Surveyor's Michigan License No. 27447

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995

