

MAR 2 0 2000

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

Mackinac County Remonumentation Corner

For corners in

Mackinac County

Located in:

Corner Code #

1. Public Land Survey

T42N R01E T42N R01W T R T R T R T R WCMC A 11/12 WCMC M 11/12 ✓

Property Controlling in Section
 Miscellaneous

3. Miscellaneous
Property in Sec.

S T R S T R S T R S T R #010

FEB 2 5 2000 AM PM 7|8|0|10|11|12|1|2|3|4|5|6 Register of Deeds Stamp & File Number

۶

G H

f

J

we

В

6 7

8

۵

10

11

12

13

0.0

32

RECEIVED & FILED

DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

4. Lot No.

, Recorded Plat

5. Private Claims

I, Neil E. Hill, in a field survey on 12-20-99, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845 GLO Notes William A Burt

8" Aspen for 1/4 post

12" Aspen S 10 W

12 lks

No Subsequent Information

ACCEPTED BY THE MACKINAC COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER PA. 345 OF 1990 AT A MEETING HELD ON 11-05-09

33

34

35

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999 No evidence of original or subsequent corners

Drilled ½" rod and Cap #27447 in bit roadway online and at GLO distance from North

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a ½" rod with cap #27447 Corner is 5.6' East of CL of N-S Roadway

Corner is 35' North of CL of Street to the East

 Pwr Pole
 S 80 W
 41.48'

 Pwr Pole
 N 20 E
 57.91'

 Pwr Pole
 Due E
 71.96'

 Pwr Pole
 S 10 E
 69.68'



Bearings are compass bearings, corrected for declination, all distances are to a double- head nail in the side of the witness object unless otherwise noted.

January 21 2000

signed by Teil E- Will PS, PC,

Date

Surveyor's Michigan License No. 27447

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 23, 1971
REVISED MAY 14, 1975