

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

Corner Code #

RECEIVED & FILED  
DIANE FRANKOVICH  
MACKINAC COUNTY REGISTER OF DEEDS

NOV - 7 1995

AM 055 PM  
7|8|9|10|11|12|1|2|3|4|5|6

1. Public Land Survey	T <u>43N</u>	R <u>1W</u>	<u>G-3</u>
	T _____	R _____	_____
	T _____	R _____	_____
	T _____	R _____	_____
2. Property Controlling in Section	S _____ T _____	R _____	_____
	S _____ T _____	R _____	_____
3. Miscellaneous Property in Section	S _____ T _____	R _____	_____
	S _____ T _____	R _____	_____

**Register of Deeds Stamp & File Number**

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, David B. Guthrie in a field survey on 8/2, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845: Established by J.W. Mullett, G.L.O. Survey - Set post and referenced  
Tamk. 8 - N57E - 10 / Fir 10 - S69W - 13

1990: Survey by Thomas Fabis - Found 5/8" Iron Rod at road intersection

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995: Found 5/8" Iron Rod at road intersection

## SURVEY & REMONIFICATION

DEC 01 1995

## CONCLUSION

ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER P.A.  
345 OF 1990 AT A MEETING  
HELD ON 9-10-95

James H. Kranger

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1995: Placed a 3" Aluminum Cap stamped to identify the corner on a 5/8"x24" Iron Rod. The corner was set 6" below the road surface.

Referenced - (Exist.) N41°E - Fe. Post - 45.73 Feet  
(Exist.) N41°W - Utility Pole - 49.41 Feet  
(Exist.) S54°W - Utility Pole - 46.90 Feet  
N65°W - Fence Post - 84.24 Feet

Signed by

Date \_\_\_\_\_

Surveyor's Michigan License No. 22435

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1977

**D - 0376**

REVISED JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

