

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Mackinac

(County)

Located In:

Corner Code #

1. Public Land Survey

T____ R____

T____ R____

T____ R____

S____ T____ R____

2. Property Controlling
in Section

S 31 T 44N R 7W 9

S 31 T 44N R 7W 13

3. Miscellaneous
Property in Sec.

S____ T____ R____

S____ T____ R____

Register of Deeds Stamp & File
Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims

13 Jun 01 2005

9 Nov 01 2005

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 31) East 1/16 corner Section 31. Not established in the original survey.
(13-Sec. 31) Southeast 1/16 corner, Section 31. Not established in the original survey.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 31) Established the corner midway and on a straight line between Quarter corner 1324.79' East and Center of Section (unmonumented) 1324.79' West. From the corner thus established, I found a metal fence post S47W 15.0' distant.
(13-Sec. 31) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx36" I.pipe with 4" alum. (13) Set 5/8"x18" rebar w/plastic cap
MDNR cap. Set measuring nails in: "MICH DNR PS33986" set flush with road
10" Maple N42W 17.7' mrkd "E1/16 BT" surface. Set measuring nails in:
9" Maple S20E 26.95' do Power pole E-35 S30E 57.3'
10" twin Maple S73E 32.3' do 5" Tamarack N64E 56.3' mrkd "SE1/16 BT"
11" twin Maple N58E 18.05' do 10" Tamarack N70W 67.5' do
Bearings are magnetic. Distances are to 6" Tamarack N21E 46.62' do
nail with tag. Center of pavement of Hiawatha Trail,
South 11.7'. Bearings are magnetic.
Distances are to nail with tag.



Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 1/26/06

For the Michigan Department of Natural Resources, Office of Land and Facilities