SURVEY & REMONUMENTATION

APR 2 8 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

C152287

94 DEC 14 AM 10: 55

or corners in COMMISSIO	N	,	CALL.	BAUGH
MACOMB	Located In:	Corner Code #	REGIT	COEEDS
(County)	STERLING HEIGHTS		MACI	TTY, M

L 31 ·

-32

. 33

--- 35 · ·- 3∂

MACOMB (County) Public Land Survey URED 6527 PAGE 864 Property Controlling R in Section T R Miscellaneous Register of Deeds Stamp & File Number Property in Sec.

Lot No, Recorded Plat	A B C D E F G H I J K L	. 1
Private Claims	2 6 5 4 3 2 "	
	3	
	4 7	
	6.	-
STEVEN E. DUNN , in a field survey on MARCH 20 , 19 94 ,		•
hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points	6 18 17 16 15 14 1	3
required in lines 1 and 2 above were in conformance with regulations and rules therefore required in the current manual of survey instructions of the United States Department of	<u></u>	
e Interior, Bureau of Land Management or by a decree of a Court of Law and for that the	8 19 20 21 22 23 2	14
mer points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the	9	
chigan Board of Land Surveyors or by a Decree of a Court of Law; established,	1C 30 29 26 27 26 2	:5

OTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

established, monumented, re-monumented, recovered, found as expressed below:

Description of original monument and accessories and/or subsequent restoration:

GLO POST - NO EVIDENCE OF ORIGINAL CORNER FOUND

GLO ORIGINAL SURVEY PERFORMED BY JOSEPH WAMPLER 1817

L.C.R.C.	NAME AND NUMBER	<u>DESCRIPTION</u>	<u>DATE</u>
L. 4800 P. 479	JOHN R. FENN, #23505	FOUND 1/2" IRON ROD	MARCH 3, 1988
L. 4377 P. 553	KENNETH S. WILKERSON, #21584	FOUND IRON IN MONUMENT BOX	JANUARY 17, 1990

PLATS

A-13 T.2N. R.12E.

L. 112 P. 7 & 8
L. 112 P. 7 & 8
L. 116 P. 20 & 21
LEHO INDUSTRIAL ACRES NO. 5
OCTOBER 1965

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-13 SECTION CORNER

COMMON TO A-1 T1N, R12E

FOUND 1/2" IRON IN MONUMENT BOX IN CONCRETE PAVEMENT.
VERIFIED LOCATION BY COMPARING FOUND WITNESSES OF ABOVE L.C.R.C.'s AND COMPARED TO ADJACENT
SUBDIVISION AND SECTION CORNERS.

FOUND WITNESS TIES
L. 4377 P. 553
SOUTHWEST SOUTHEAST 73.40" PK IN NORTH FACE OF UTILITY POLE
NORTHWEST 84.84" RAILROAD SPIKE IN EAST FACE OF UTILITY POLE
NORTHEAST 70.89" CENTER OF SANITARY MANHOLE

NORTHEAST 70.891 CENTER OF SANITARY MANHOLE

L. 4800 P. 479 N.40°W. 86.401 FOUND PK IN WALK

FIELD MEASUREMENTS AND RECORDED DISTANCES A-13 TO NORTHWEST CORNER "LEHO INDUSTRIAL ACRES NO. 5" L. 116 P. 20-21 (O.C.R.) 1621.75' (M.) 1621.84' (R.) A-13 TO M-2, T.1N., R.11E. 2832.48' (M.) 2835.42' (R.) "LEHO ÍNDUSTRIAL ACRES NO. 4" L. 112 P. 7 & 8 (O.C.R.)

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

		STAMPED "MACOMB COUNTY MONUMENT MI. ACT 349	#28408" IN AN EXISTING MONUMENT BOX.
VITNESSES			
AZ. 24°	84.95'	SOUTHWEST BOLT OF TRAFFIC LIGHT BASE	ACCEPTED BY THE MACONIB COUNTY SURVEY PEER
AZ. 132°	73.38	PK NAIL IN NORTH FACE OF UTILITY POLE	GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1890 AT A MEETING HELD
AZ. 245°	81.36'	NORTHEAST BOLT OF TRAFFIC LIGHT BASE	ON 10-18-94
AZ, 319°	84.77'	RAILROAD SPIKE IN EAST FACE OF UTILITY POLE	Wellia Etodeby
			WILLIAM E. SODERBERG, P.S., CHAIRMAN*

I REPLACED 1/2" IRON BOD WITH A 3/4" x 24" IRON BOD WITH 2" DIAMETER ALLIMINUM CAP

EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER	D BY PROFESSIONA	L SURVEYORS AS I	HE BEST AVAILABLE	
ned by Sterren E. Dunn	Date <u>Nov.</u>	12,1994	1	
veyor's Michigan License No. 28408				