

SURVEY &  
REMONUMENTATION

APR 28 1995

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

C152254

94 DEC 14 AM 10:54

COMMISSION

or corners in

MACOMB

(County)

Located In: Sterling Township Corner Code ##

Public Land Survey

T 2N R 12E G-6

T R

T R

T R

Property Controlling

S T R

in Section

S T R

Miscellaneous

S T R

Property in Sec.

S T R

LIBER 6527 PAGE 831

Register of Deeds Stamp & File Number

Lot No. , Recorded Plat

Private Claims

Randy Kolehose in a field survey on July 28, 1994

hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as pressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

3-6	1817	G.L.O.	Notes	Wampler	NA	Post
	1978	L.C.R.C.	L. 2936 P. 225	Hooth	#7966	Conc. Mon. in Mon. Box
		MCRC	File #72	NA	NA	1" Iron

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

3-6 Found concrete monument 24" ± below ground surface in monument box in center line median of Van Dyke Road. Checks closely to measurements north and south per MDOT.

All witnesses have been destroyed.

Measure N. 2741.85 to G-5 (MDOT 2741.33) (G.L.O. 2640)  
Measure S. 2608.56 to G-7 (MDOT 2608.08) (G.L.O. 2640)

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 8-16-94

WILLIAM E. SODERBERG, P.S., CHAIRMAN

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3-6 I placed a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345 #25854" over the existing Concrete Monument, in an existing Monument Box.

PK NE Face Util. Pole N 65° W 102.00'  
"4" Center Line Top Nut Hydrant S 37° W 188.85'  
PK SW Face Util. Pole S 25° E 115.93'  
PK S Face Util. Pole S 83° E 61.10'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

igned by Randy J. Kolehose  
urveyor's Michigan License No. 25854

Date 10/14/94

