

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

SURVEY &  
MONUMENTATION

FEB 27 1997

COMMISSION

Register of Deeds Stamp & File Number

For corners in

MACOMB  
(County)

Located in: City of Corner Code #  
Sterling Heights

Public Land Survey

T 2N R 12E G-9  
T R  
T R  
T R

Property Controlling  
in Section

S T R  
S T R

Miscellaneous

S T R

Property in Sec.

S T R

Lot No. , Recorded Plat

Private Claims

Randy Kolehose, in a field survey on May 24 19 96

I hereby certify that under requirements of P.A. 74 Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

-9	1817	G.L.O. Notes	Wampler	N/A	Set Post
	N/A	MCRC File No. 111	N/A	N/A	1" Iron
	1975	L.C.R.C. L. 2627 P. 867	McMahon	#4018	Iron in Handhole
	1980	Cert. Survey L. 3281 P. 839	Merdzinski	#10697	Iron
	1980	Cert. Survey L. 3292 P. 783	Merdzinski	#10697	Iron
	1989	L.C.R.C. L. 04723 P. 602	Donnelly	#21563	1" Iron in Monument Box

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

-9 I found a boat spike in a monument box in the C/L of 16 Mile Road (conc.) westbound and 17' ± West of the C/L of VanDyke Road (conc.) northbound which checks with the witnesses listed below. No witnesses remain from Wampler's G.L.O. notes, the Macomb County Road Commission records, Cert. Survey L. 3281 P. 839 or Cert. Survey L. 3292 P. 783. This corner checks closely to MDOT distances to G-8, H-9 and F-9.

L.C.R.C. L. 04723 P. 602

Az. 50 deg. 93.81' PK w/ RJD tag SE face UP (m. 93.75')

Az. 126 deg. 88.59' PK w/ RJD tag in NE face UP (m. 88.81')

Az. 233 deg. 136.54' PK w/ RJD tag N face UP (m. 136.51')

Az. 298 deg. 125.26' PK w/ RJD tag NE face UP (m. 125.11')

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER  
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
ON 9-17-96

William E. Soderberg, P.S., CHAIRMAN

Measure East 2665.82' to H-9 (G.L.O. = 2583.9') (Plats = 2666.83') (MDOT = 2665.21')

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

-9 I replaced the found boat spike with a 3/4" x 24" iron rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345 #25854" in an existing monument box.

N 57° E 93.75' - Found P.K. Nail w/Tag "Donnelly #21563" SE Face Util. Pole

S 13° E 220.92' - Found "+" NW Bolt Hydrant Flange

S 60° W 136.51' - Found P.K. Nail w/Tag "Donnelly #21563" NW Face Lt. Pole

N 55° W 125.11' - Found P.K. Nail w/Tag "Donnelly #21563" NE Face Util. Pole

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.



Surveyed by Randy J. Kolehose

Date 11/19/96

Surveyor's Michigan License No. 25854

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983

C0458232 LIBER:07298 PAGE:265 10:47A 01/02/1997  
CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

637