

## REMONUMENTATION

APR 28 1995

C0158358 LIBER:06543 PAGE:380 08:35A 01/05/1995  
CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MACOMB

(County)

Located In:  
CLINTON

Corner Code #

1. Public Land Survey

T 2N R 13E

C-11

T R

T R

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

Register of Deeds Stamp &amp; File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, STEVEN E. DUNN, in a field survey on APRIL 15, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO POST - NO EVIDENCE OF ORIGINAL CORNER FOUND

GLO ORIGINAL SURVEY PERFORMED BY PRESTON 2-18-1818

## CERTIFICATE OF SURVEY

L. 3169 P. 3

ROBERT L. SMITH, #16052

OCTOBER 13, 1979

## L.C.R.C.

L. 2879 P. 823

JOHN J. MCMAHON, #4018

FOUND MONUMENT BOX

L. 3020 P. 436

TREVOR N. PARISH, #24609

FOUND MONUMENT BOX

L. 3081 P. 922

JOHN J. MCMAHON, #4018

FOUND 1/2" IRON BAR IN MONUMENT BOX

L. 3579 P. 143

HERBERT J. KOBS, #14097

FOUND 5/8" IRON BAR IN MONUMENT BOX

L. 4723 P. 615

RAYMOND J. DONNELLY, #21563

FOUND 5/8" IRON ROD IN MONUMENT BOX

L. 5107 P. 556

JOHN R. FENN, #23505

FOUND 5/8" IRON IN MONUMENT BOX

ACCEPTED BY THE MACOMB COUNTY SURVEY PEI  
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
ON 12-13-94

William E. Soderberg, P.S., CHAIRMAN

NOVEMBER 15, 1977

OCTOBER 23, 1978

MARCH 26, 1979

JANUARY 3, 1984

SEPTEMBER 15, 1989

MAY 22, 1991

SEE SHEET 2 OF 2

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-11 SECTION CORNER

FOUND 5/8" IRON ROD IN MONUMENT BOX IN CONCRETE PAVEMENT

VERIFIED LOCATION BY COMPARING FOUND WITNESSES OF L.C.R.C.'S AS LISTED BELOW:

## FOUND WITNESSES

L. 2879 P. 823

N.45°W.

82.20'

TOP BOLT ON FIRE HYDRANT

S.45°W.

82.80'

TOP BOLT ON FIRE HYDRANT

L. 3020 P. 436

N.45°W.

82.20'

TOP BOLT ON FIRE HYDRANT

S.45°W.

82.80'

TOP BOLT ON FIRE HYDRANT

L. 3081 P. 922

N.49°E.

53.40'

NAIL AND WASHER IN WOOD POLE

L. 3579 P. 143

NE

41.82'

CHISELED CROSS ON SOUTHWEST RIM OF MANHOLE

SOUTH

16.45'

CHISELED CROSS ON NORTH RIM OF MANHOLE

SW

62.75'

TOP CENTER OF FIRE HYDRANT

NW

82.42'

TOP CENTER OF FIRE HYDRANT

SEE SHEET 2 OF 2

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11 T.2N., R.13E.

I REPLACED 5/8" IRON ROD WITH 3/4" x 24" IRON ROD WITH 2" DIAMETER ALUMINUM CAP  
STAMPED "MACOMB COUNTY MONUMENT MI. ACT 345 #28408" IN AN EXISTING MONUMENT BOX.

## WITNESSES

S.04°W.

16.38'

FOUND SCRIBED "+" ON SOUTHWEST RIM OF MANHOLE

S.52°E

92.86'

FOUND PK NAIL WITH TAG #21563 IN NORTHEAST FACE OF UTILITY POLE

N.58°W.

82.32'

CENTER TOP NUT OF FIRE HYDRANT

S.04°W.

02.66'

CENTER TOP NUT OF FIRE HYDRANT

N.48°E.

53.50'

FOUND PK NAIL AND WASHER IN NORTHWEST FACE OF UTILITY POLE

S.50°W.

73.35'

FOUND PK NAIL WITH TAG #21563 IN NORTHWEST FACE OF UTILITY POLE

THE SELECTED LOCATION IS ACCEPTED BY ME AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST  
AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Steven E. DunnDate Dec 20, 1994Surveyor's Michigan License No. 28408

A. Description of original monument and accessories and/or subsequent restoration:

M.C.R.C. WITNESS CARDS (UNRECORDED)

NO NAME	1" SOLID IRON	JANUARY 4, 1930
NO NAME	MONUMENT BOX	1959

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND WITNESSES

L. 4723 P. 615	AZ. 123°	92.89'	SET PK NAIL AND TAG IN NORTHEAST FACE OF UTILITY POLE
	AZ. 224°	73.59'	SET PK NAIL AND TAG IN NORTHWEST FACE OF UTILITY POLE
	AZ. 297°	82.34'	CENTERLINE OF TOP BOLT ON HYDRANT
	AZ. 43°	53.58'	FOUND NAIL AND TAG IN NORTHWEST FACE OF UTILITY POLE
L. 5107 P. 556	SW	73.44'	PK WITH TAG #21563 ON NORTHWEST FACE OF UTILITY POLE
	SE	92.91'	PK WITH TAG #21563 ON NORTHEAST FACE OF UTILITY POLE
	SW	62.68'	TOP OF HYDRANT
	NW	82.31'	TOP OF HYDRANT

FIELD MEASUREMENTS AND RECORDED DISTANCES

C-11 TO B-11	2712.72' (M.)	39.95 (GLO)	2636.70'
C-11 TO D-11	2698.73' (M.)	39.95 (GLO)	2636.70'
C-11 TO C-12	2648.98' (M.)	40.00 (GLO)	2640.00'

ACCEPTED BY THE MACOMB COUNTY SURVEY REE  
GROUP AS THE OFFICIAL CORNER UNDER MICHIG  
PUBLIC ACT 346 OF 1980 AT A MEETING HELD  
ON \_\_\_\_\_

WILLIAM E. SODERBERG, P.E., CHAIRMAN