

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

MAR 17 2000

For corners in

<u>Macomb</u> (County)	Located in: Clinton Twp.	Corner Code # <u>F-09</u>
1. Public Land Survey	T <u>2N</u> R <u>13E</u>	
	T <u>    </u> R <u>    </u>	
	T <u>    </u> R <u>    </u>	
	T <u>    </u> R <u>    </u>	
2. Property Controlling in Section	S <u>    </u> T <u>    </u> R <u>    </u>	
	S <u>    </u> T <u>    </u> R <u>    </u>	
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	
	S <u>    </u> T <u>    </u> R <u>    </u>	

SECTION

1182  
LIBER 9275 PAGE 534  
01/04/2000 09:29:27 A.M.  
MACOMB COUNTY, MI  
CARNELLA SABAUGH, REG/DEEDS

Register of Deeds Stamp & File  
Number

4. Lot No.         , Recorded Plat           
5. Private Claims         

I, Michael S. Hoben, in a field survey on April 16, 1999  
do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points  
mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required  
in the current manual of survey instructions of the United States Department of the Interior, Bureau of  
Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines  
3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by  
a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed  
below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-09 1817 GLO Notes	Wampler	NA	Post
1946 "Kelly-Nunneley Subdivision"	L.23, P.24	NA	
1969 "Chippewa Subdivision"	L.60, P.37	NA	
1972 LCRC L.2338, P.764	William Carlson	14759	Set
1/2" iron			
1983 LCRC L.3895, P.538	George G. Jerome	19837	FD. 1/2" iron
1993 LCRC L.6257, P.728	Patrick L. Hastings	37277	FD. 1/2" iron

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-09 Found 1/2" rebar in centerline of Metro Parkway median (16 Mile Road) in line with a wall to the south

L.C.R.C. L.3895, P.538; L.2338, P.764  
SE 34.63' & 35.14' Found tag northeast face 10" Ash (Set MCR tag above (m 34.69'))  
SW 33.71' & 33.06' Found tag northwest face 18" Ash (Set MCR tag above (m 33.69'))  
NE 51.03' Found PK Nail in centerline joint west bound Metro Parkway (m 50.91')  
S6W 150.22' & 150.00' Found conc. Monument (m 150.11')

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-09 Replaced 1/2" rebar in centerline of Metro Parkway median (16 Mile Road) on wall line to south with a 4"x 48" concrete  
monument w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345 #35994".

S 58° E 34.69' Set mag nail w/ Remon. tag northeast face 10" Ash  
S 60° W 33.69' Set mag nail w/ Remon. tag northwest face 18" Ash  
N 5° E 50.91' Found PK nail in centerline joint west bound Metro Parkway  
S 6° W 150.11' Found conc. Monument  
S 12° W 149.21' Set mag nail w/Remon. tag west face P.P.

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER  
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
ON 10/26/99  
William E. Soderberg  
WILLIAM E. SODERBERG, P.S., CHAIRMAN



The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence  
of the position of the original corner.

Signed by Michael S. Hoben  
Surveyor's Michigan License No. 35994

Date Dec 27, 1999

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 199

224