C0824459 LIBER:08436 PAGE:182 09:43A 11/20/1998 CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

LAND CORNER RECORDATION CERTIFICATE

_	_	riling Red	fairement of A	ict /4, Mic	n. P.A. 1970	*				
For corners	in					j				
Maco	mb	Located In:	Corner Cod	# ۵		;	SUTTV	TY A		
(Coun			Comer Cou	C 17		Cont. Com	MORUM	Ellings from	779 D 5	
(000)	•11	Shelby Twp.				li b.	MENNING CITY	LL, N. E	14	
1. Public La	nd Survey	T 3N. R	12E. [0-7			MAR 1	1000		
		T R					MARIA SE C	1999		
		T R								
		<u> </u>					dia Pina			
	• • •	<u> </u>			j		SECT	ION		
2. Property	_	S T R			j			C 1 (
in Section	1	S T R								
3. Miscellan	eous	s r R								
Property		S T R								
roporty	iii 000.	· - ' - ' \								
		ACCEP	TED BY THE MACC	MB COUNTY	SURVEY PEER	Regis	ter of Deeds	Stamp & Fil	e Number	
		CBOUR	AS THE OFFICIAL	CORNER UN	DER MICHIGAN					
4. Lot No	, Record	ded Plat PUBLIC	ACT 345 OF 1	990 AT A N	IEETING HELD					
5. Private C	laims	ON	10/13/98	0/		1 A B	CDE	<u> </u>	JKLN	
			2 102 5	1/2-17		- 1 1				
		_ <i>U</i>	al my	1000		2 6		ı —— 3 —	– 2 – 1 –	
			WILLIAM E. SODER	Berg, P.S., C	HAIRMAN	3 4		. .	į	
						-				
I, Jeffrey A	. Wright	, in a field survey on	24 August . 1	19 98 do her	eby state that under	4 7 -	 8 9) —— 10 ——	- 11 12	
requirements of	of P.A. 74, Michiga	an P.A. of 1970, the co	rner points mentione	ed in lines 1 a	ind 2 above were in	ااء	1 1 1		1 1	
requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the										
United States D	Department of the Ir	nterior, Bureau of Land	Management or by a	a decree of a	Court of Law and/or	6 - 18	17 11	6 - 15 -	- 14 + 13 -	
that the corner	points mentioned is	n lines 3, 4 and 5 above	were in conforman	ce with the rul	es of the Michigan	7				
Board of Land	Surveyors or by	a Decree of a Court	of Law; established	d, re-establis	hed, monumented,	, <u> </u>				
recovered, foun	d as expressed bel	low:				8 - 19	⊥ 20 ⊥ 2	1 - 22 -	_ 23 🚣 24 _	
NOTE: NA						ا أم				
		rners, all in the sa	me town and rar	nge, may b	e recorded	9				
on	this certificate.					10 - 30	1 29 1 2	8 1 27	- 26 - 25 -	
						K 1			1 2	
						11	 - -			
						12 - 31	32 4 3	3 34	- 35 36 -	
								7 7 7	- 35 36	
						13				
 A. Description 	on of original m	onument and acces	ssories and/or su	ıbsequent r	estoration:					
						į				
	Date	Surveyor	Number	Type		L.	₽.	Monument	t Boy	
				, , , , ,			• •	WO GATTER	. 50%	
	4047	181								
		Wampler		Set Post		GLO Rec	ords	No		
	1974	Pawlaczyk	17632	F. cut nail	Act 132	2544	849-851	No		
	1974	Pawlaczyk	17632	F. cut nail	Act 74	2544	852-853	No		
	1975	Kobs	14097	Unknown	Act 132	2640	924	Unknown		
	1987	Kobs	14097	Unknown	Act 132	4306	737-738	Unknown		
	1990	Avey	15396	F. 1/2" bar	Act 74	4983	759	No		
	1996	Marini	26462	F. 1/2" bar	Act 74	7168	88	No		
B. Description	on of carner evi	dence found and/o	r method applied	in restorin	or reestablishi	na corner	:			
·					,		•			
	Found 1/2" har as	e previously recorded			Graved Dia	tonooo:				
Found 1/2" bar, as previously recorded. (Located at the int. of 23 Mile Rd. & Shelby Rd.) Ground Dis GLO: D-7 tr										
			iby Ka.)			to C-7 = 80.10 ch. (2643.3') ' = 2744.87' m.				
	Location suppo	rted by corners in:			D-7 to C-7					
	Maeder Sub. #1	1	L. 27, P. 45		GLO: D-7 to	0 E-7 = 80	0.70 ch. (2663	.1')		
	Shelby Highland Sub. #1			L. 29, P. 20 D-7 to E-7						
Shelby Highland Sub. #2			L, 33, P. 21							
					to centerline			704)		
	Shelby Highlan		L. 27, P. 21		& Shelby R	a. = 10.25	' r.&m. (AZ. 27	/UT)		
	Evergreen Acre		L. 28, P. 31							
	Maeder Sub. #2	2 i	L. 28, P. 25		Chestnut Ridge	e Sub.	L. 53, P.	12		
C. Descripti	on of manumen	t for corner and ac	reconiec establi	shed to ner	netuste locating	the noci	tion of the o	OFF OFF SEE		
o. Beeripa		it for corner and ac-	Jeggorieg egtabli	shed to per	petuate locating	tile posi	uon or the ot	<i>3114</i> 00000	IIIIIII	
	0-4-0740 5-2-1-3	41				:	1111	OF M	C. Wille	
	Set 3/4" par wi	th an aluminum cap	o stamped "Macc	omb County	Monument - Mi	Act 345	#4016 50 0	k,	70.1/	
	in a new monur	ment box.				9	S &		4 1	
							= ₹ * ;	· JEFFREY	(A.) + =	
	78.09' (AZ, 218°)	to centerline bolt @ N	E corner of N base	of Total das	station sign		= :	WRIGH	iT % ★ 🗏	
C. Description of monument for corner and accessories established to perpetuate locating Set 3/4" bar with an aluminum cap stamped "Macomb County Monument - MI in a new monument box. 78.09' (AZ. 218°) to centerline bolt @ NE corner of N base of Total gas station sign 66.98' (AZ. 133°) to centerline top hydrant 52.83' (AZ. 129°) to MAG nail w/ Macomb County Witness Tag in NE side U. pole 46.73' (AZ. 28°) to MAG nail w/ Macomb County Witness Tag in SE side U. pole 90.38' (AZ. 292°) to MAG nail w/ Macomb County Witness Tag in SW side U. pole 10.25' (AZ. 270°) to MCRM #40165 in monument box (CL int.) The selected location is accepted by me and is generally accepted by Professional Surveyors as the best position of the original corner.							= = ;	PROFESSIO	MAL 🖁 📜 🗏	
							≘ 6 €	SURVEY	OR !ÖĒ	
							三星	No.	. / \$ 3	
40.73 (AZ. 201) to MAG hall W/ Macomb County Witness Tag in SE side U. pole							1000	4016	E. E.	
	90.38' (AZ. 292°)	to MAG nail w/ Macor	nb County Witness	Tag in SW	side U, pole	•	The state of	PAO:	" 25 MIL	
	10.25' (AZ. 270°)	to MCRM #40165 in r	nonument box (CL	int.)			141	JUFESSIO	NY IIII	
The selected in	ocation is accepte	d by me and is denera	lly accepted by Pro	Diessional Su	vevors as the hee	t availahle	evidence of the	<i>(4)</i> /////	IIIII.	
nosition of the	original corner.		,		, 23 410 000		- madrice of ult	*	-	
20010011 OI U18	Ungillar Corrier.	1101	\mathcal{I}			1		_		
A1 4.1		MIN	D-L			コ	NOVEMB	ED W	7 0	
Signed by		1900.00	10/0		Date:	14	טואושיטין	r pp	70	
	07									
Surveyor's N	lichigan License	e [®] No. <u>40165</u>								