SURVEY & REMONUMENTATION

APR 28 1995

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

C152191

or corners in		
(County)	Located In: Shelby Corner Code ##	LIBER 6527 PAGE 768
Public Land Survey	T 3N R 12E	94 DEC 11, AM 10: 50
Property Controlling in Section Miscellaneous Property in Sec.	S T R	REGIONAL DEEDS MACCO Stamp & File Number
Lot No,	Recorded Plat	A B C D E F G H J K L M
hereby certify that under re- tines 1 and 2 above were trent manual of survey inst nagement or by a decree of ove were in conformance wourt of Law; established, pressed below:	n a field survey on June 15, 1994 equirements of P.A. 74, Michigan P.A. of 1970, the corner points mention in conformance with regulations and rules therefore as required in fructions of the United States Department of the Interior, Bureau of La Court of Law and/or that the corner points mentioned in lines 3, 4 and with the rules of the Michigan Board of Land Surveyors or by a Decree re-established, monumented, re-monumented, recovered, found corners, all in the same town and range, may be recorded	the and 7
on this certificate	monument and accessories and/or subsequent restoration:	12 31 32 33 34 35 36 13
1817-GLO Wampler, D.S.; 7" Beech N20*W 4 I	Set Post on the Township line 0.73 chains West of Found Posinks; 10" Beech S56*E 22 Links 10092; LCRC L.5643, Pg.662 - Fnd 5/8" Pipe in a Monument Box	·

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

994 Kennedy Surveying, Inc. - Kennedy, P.S. #17623 - Fnd 5/8" Iron Pipe in a Monument Box in the centerline of 26 Mile Road, which has a bituminous surface, and Jewell Road to the South, which has a gravel surface. Jewell Road to the North, which has a gravel surface and is staggered 45.80' East. The Northeast corner of Section 3 Town 3 North, Range 12 East, is 45.80' West of the Southeast corner of Section 34, Town 4 North, Range 12 East.

Witnesses from the first LCRC were used to recover and verify the location of the found 5/8" Iron Pipe in a Monument Box.

FIELD MEASUREMENT BETWEEN

I-1 to J-1 2686.54 Feet I-1 to H-1 2549.21 Feet

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD

WILLIAM E, SODERBERG, P.S., CHAIRMAN

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

ON

-1	I replaced the found 5/8" Iron Pipe in a Monument Box with a 3/4" x 24	f" Iron Rod w/2" diameter aluminum	cap stamped "Macomb County
	Monument" MI Act 345 #17623 in a existing Monument Box.	,	
	S44 E 43.82' Set PK & Remon. Washer NE face Power Pole		
	571'E 75.69' Set PK & Remon. Washer NE face 21" Walnut	•	WHITE OF BALL STATE
	N53'E 100.55' Set PK & Remon. Washer SE face Power Pole		A CONTRACTOR OF THE PARTY OF TH
	N27'E 41.30' Set PK & Remon. Washer SE face Power Pole		MENTE OF MICHELLE

he selected location is accepted by me and is generally accepted by Professional Surveyors as the best sition of the original corner.

Date 20 17623 eyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYDRS, JAN. 28, 1971 REVISED MAY 14, 1975

REVISED JAN., 1983