

# LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Macomb

(County)

Located In: Washington Twp

Corner Code #

SURVEY &  
REMONUMENTATION

FEB 27 1997

COMMISSION

Register of Deeds Stamp & File Number

1. Public Land Survey

T4N R 12E

I-2

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling  
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Huston K. Kennedy, in a field survey on May 8, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

C0458222 LIBER:07298 PAGE:255 10:47A 01/02/1997  
CARMELLA SABAUGH-MACOMB COUNTY, MI REG/DEEDS

A. Description of original monument and accessories and/or subsequent restoration:

1817-GLO Wampler, D.S.; Set Post 11" Birch S20°E 36 Links; 9" White Oak N52°W 37 Links

1.) 1976-Kobs, PS #14097; LCRC L.2750, Pg.602 - Fnd 1/2" Pipe in pavement

2.) 1990-Avey, PS #30076; LCRC L.4795, Pg.484 - Fnd 1/2" Pipe in pavement

3.) 1976-Kobs, PS #14097; Survey L.2750, Pg.601 - Fnd 1/2" Pipe, used same wit as 1976 LCRC

4.) 1979-Alloway, PS #12043 Survey L.3127, Pg.751 - Fnd Iron, no witnesses

5.) 1980-Kobs, PS #14097; Survey L.3252, Pg.322 - Fnd 1/2" Pipe, used same wit as 1976 LCRC

6.) 1987-King, PS #30085; Survey L.4306, Pg.749 - Fnd 1/2" Pipe, used same wit as 1976 LCRC

ACCEPTED BY THE MACOMB COUNTY SURVEY PEE  
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN  
PUBLIC ACT 345 OF 1990 AT A MEETING HELD  
ON 5-21-96

William E. Soderberg  
WILLIAM E. SODERBERG, P.S., CHAIRMAN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1996 Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd 1/2" Iron Pipe 3" deep in the existing centerline of Sisson Road extending to the North & South, which has a bituminous surface.

Witnesses from LCRC #1 & 2 were used to recover and verify the location of the found 1/2" Iron Pipe.

## FIELD MEASUREMENTS BETWEEN

I-2 to I-3 GLO = 40 chains or 2640.00 Ft. & 2621.10 Ft. (GPS-MEA) 2621.34 Ft., L.2750, Pg.601  
I-2 to I-1 47.97 chains or 3166.02 Ft. & 3184.99 Ft. (GPS-MEA)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2 I replaced the found 1/2" Pipe with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345"  
#17623 in a new Monument Box  
S87°W 31.88' Set PK & Remon Washer North face Power Pole  
S88°E 55.68' Set PK & Remon Washer North face 13" Ash  
N36°E 119.85' Set PK & Remon Washer NW face 8" Maple  
N42°E 59.40' Set PK & Remon Washer SE face 18" Maple

The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by [Signature]  
Surveyor's Michigan License No. 17623

Date 12-6-96

