LAND. CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

COMMISSION

For corners in		*			
Manistee	Located in:	Corner C	ode <i>=</i> ##	REGISTER'S OF	FFICE
(County)				MANISTEE COU	NTY
	т <u>^{24N}</u> в _	16W G-	5 M.C.	#93-64	OAT 10:10 A.M
Public Land Survey				NOV 3 1	993
	T R			^ ······	
	T R)	Penny a.	Porch
	T R	(Uther	- H	REGISTER OF I	I-CLAS
2. Property Controlling	S T R	`		neg sien of a	, , , , , , , , , , , , , , , , , , ,
in Section	S T R				4
3. Miscellaneous	S T R _	<u> </u>		Register of Deeds Stan	n & File Number
Property in Sec.	S T R			register of Deeps Stall	ib a Life Manipel
	-				· · · · · · · · · · · · · · · · · · ·
4 Lot No	Recorded Plat				*
				A B C D E (FGHIJKLW
5. Flivate Claims			· · · · · · · · · · · · · · · · · · ·	2 1 1 1	
				3 1 1	
					7
Richard L. Ha	ys _, in a field survey on	ctober 27	93	4 - 7-1-8-1-9	10-11-11-12-
,	in a field survey on		, 19	5	
	equirements of P.A. 74, Michig			6 18 17 1	5-15-14-13-
	in conformance with regulati			7	
	tructions of the United States of a Court of Law and/or that the			8 19 20 2	
	with the rules of the Michigan I	•	•		1-1-22-1-23-1-24-
	re-established, monumente			9	
expressed below:	,			10 30 29 28	8 27 26 25
NOTE: Not more than 4	corners, all in the same to	own and range, may	be recorded	11	
on this certificate	•	,		12 1 3 3	
011 11110 001 1111,0001	-			13	
A Description of origina	I monument and accessori	es and/or subseque	nt restoration:	/V <u> </u>	as as
G-5	MEANDER CORNER COM	MON TO SECTION	5 9 & 16		₩.
	G.L.O. Set Post, N			,	i 80,7
					£ 7 0 C
1967, The Plat of	Star Key Point	1987, US Corps	of Engineers	Drawing	Σ .૦ઁ૦
Subdivision shows		(# S167-86-000	R) shows an II	ron at	, 4 , 7
Corner 2985.61' We		2798.88' West			50.2
		of Section 10.	or circ Horeir a	1/1 0011101	+ ou >
1/4 Corner of Sect		NO WITNESSES			9±4.9
NO WITNESSES		NO MITIMEDODED			크눈이다
					انخ نے تا ق
B. Description of corner	evidence found and/or me	thod applied in rest	oring or reestablish	ling corner:	ratif urs P.
			a o c 16	•	_ 5 5 5 5
G-5	MEANDER CORNER COM	MON TO SECTION	2 3 % TP	1 41 - 6) D
1993 Found 3	3/4" Iron Pipe in t	he Center line	of Gravel Roa	ad that	5 2 8
fits the Cor	rps of Engineers Dr	awing. Which	is 168' West	to Lake	• ၂၉ မ မ
Michigan and	1 58' East to Arcad	ia Lake. Foun	d an Iron set	by Anthony	0 0 5
Slawinski 33	3.70' East and an I	ron set by Bru	ce Jenema 38.9	90'West.	چا
					Date of the
					. Ωνφάν. Πι
				•	2 1 8 5
				•	7 + d
					Corner County 1915, amenda
		•			3 7 6
					. ↓OO₽ ā
				•	
C. Description of manum	ent for corner and accesso	orice cetablished to	nemetuate locating	the position of the corr	ier:
5. Description of monuti	ent for comer and access	Ales established to	perpendant recurring	y the position of the con	The state of the s
A F	RATIONAL CONTRACTOR COMMA	אראז יוור פיביייוודריאו	g Q £ 1£	A Comment of the Comm	CA MAC
G-5	MEANDER CORNER COM	and to decitor	s a a a monador	r Corner	ROWS
Set Maniste	ee County Monument	amont is seen	ntoder of the beta	et with	LIMYS .
on the Sect	ion Line. This Mo	nument is acce	pueu as une de	-a }	LAND E
available e	evidence of the pos			· 计算	2.
		= -	11.73'	1	ECHARICE 128
	10" Maple		16.00'		noi / F
	11" Red Pine		66.88'	A Strike	11.047 M
	10" Red Pine	S-74°-E 1	27.48'		A DELLO BU
In Center 1	ine of Gravel Road se. The Meander corr	168' West to	Lake Michigar	n and 58' East	Market Sign
Arcadia Lak	e, me meander corr	er or rue kecc	AUGU FIAL OL	near well torrir on	TOTAL A TOTAL TOTAL TOTAL

falls in Lake Michigan 186 ft. from the witness corner set

Surveyor's Michigan License No. 25847

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983