MAR 1 6 1998

SECTION

For corners in

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

ADAPTED FOR WORD PROCESSING MARCH, 101

FILED

For corners in MASON	Located In:	Corner Code #	1 3	:oc	من د د	ick	J)	. RA	1
(County)					4.0	Matti arm	it	IVI	
1. Public Land Survey	T_19N_R_16W	1-1		1	1	1997			
	TR			1					
	TR			j fakti Man	-cbEi SON C(a RULA MILLIA	131(1		
Property Controlling in Section	S T R			REGIS	TER O	FDEE)S		
3. Miscellaneous	S_T_R		Regist	ter of D	eeds S	tamp 8	k File I	Numb	er
Property in Sec.	STR		<u> </u>			·····			
4. Lot No. , F 5. Private Claims	Recorded Plat		1	A B	C D	E F 6) H]	JK	Li
		وروده و و و و و و و و و و و و و و و و و و	2	6	5	4	3	2	i
! Kannath I. Poss	in a field ever	oven Ostaben 24 10 0	3 7. 4) .					<u> </u>
1, Kenneth L. Ross , in a field survey on October 24, 19 97 . do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5					8	9	10	11	12
					17	16	15	IA	13
above were in conformance in	with the rules of the Michigan Board	of Land Surveyors or by a Decree	of a	1	20	21	22	23	21
expressed below:	I, re-established, monumented, re	-monumented, recovered, found	88 0		20	21		20	
NOTE: Not more than	4 corners, all in the same tow	n and range, may be record	ed to	30	29	28	27	26	25
on this certifica	ate.		1 <u>1</u> 12	1	32	33	34	35	36
	nal monument and accessories a for Sections 2 and 3, on T		: 13		102	33			
1838, Sylvester	·	1966, Robert A. G		# 13854	1				
	Note missed corner to	Found 3/4" Iron F for Sections 3 an	ipe 60" lone	g, cal	Ϊa it t			corne	r,
#1 Beech 16" 8	11° E 6 lks. (3.96 ft.) 82 W 56 lks. (34.32 ft.)	1996, Kenneth Ros				* .7			
1918, C. R. Mit	chell, Mason County Surveyor	Found 1" Iron Pip #3 Fower Pole 8 2		_ £t.					
	by Stone and Testimony Book 2 , Page 224-225	#4 Ext. "BT" Mapl #5 USFS Post w/si			.				
		#6 USFS Conc. Monu 34 £ 35, T20N-R		ss cap, 6.57		on corr	er fo	r Sect	:Lons
	er evidence found and/or method			er;					
	for Sections 2 and 3, on T	•							
of 6.57 ft. East of the	24, 1997, I Ken Ross and Ke he standard corner for Sect	ion 34 & 35, T20N-R16W. C	orner lies a						
Road (Stephens). I fo	ound no other evidence to d	ispute the location of th	is corner.						
		#1 Gone #2 Gone #3 Found in good condition	Found in go	ood cor	dition	#4	Foun	d in ç	pood
condition #5 Found	A IN EAST CONDICION #0	Found in good condition							
	·								
C. Description of monu	iment for corner and accessories for Sections 2 and 3, on Ti	s established to perpetuate loo he Township line, Ti9N-Ri	cating the pos इम.	ition of	the con	ner:			
long, with an 2 1/2" a	/4" Iron Pipe, in the exact aluminum cap, stamped to ide position of the original co	entify the corner. And i	d Hason Cour s accepted a	ity Mor as a ca	nument, reful	(5/8″ and £a	ze-r Lithfu	od, 24 1 xe-	t r
Ext "BP" #3 Power Po		(Ext. 60d spike SE side of	f pole)					* * *	
Ext "BT" #4 Maple	10" N 18" E 61.05 ft. x 1.5 ft. wide "X" chisele	(Ext.10" dock spike in SI ed in top N 51° W 44.0°		ce)					1111
Maple 26" N 58° W		in SW side of tree)			* * * * * * * * * * * * * * * * * * * *	, ,	2	**	
						1		, . , .	*
رہسب			j.		1.81	rii. Nii yes		ژ. دوران	•
Signed by	Mora	Date	lov. 6,	199	9 2"	11/11	()	7,11,	
Surveyor's Michigan Licer	nse No. <u>17634</u> <u>Peer Co</u>	: भा तिमानिकाण्यः । । । । । । । । । । । । । । । । । । ।	FORM APPROVED	шү месінде	N STATE BO	ARD OF LA		VISED MA	Y 14, 197:
	Pose: And	6,027			ADAPT	FO FOR WO		REVISED J	JAN., 1981
	Kom.	TO DE	LIBER		A PAI	n r 1	1 /1 (Ú.	