

SURVEY MECOSTA COUNTY REMONUMENTATION PROGRAM  
REMONUMENTATION

CORNER APPROVED BY PEER GROUP ON FEBRUARY 13, 1998

OCT 26 1999

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN  
COUNTY OF MECOSTA  
RECEIVED FOR RECORD

For corners in SECTION

MECOSTA  
(County)

Located In:

Corner Code #

'99 JUL -2 P2:59

*Joanne Brown*  
REGISTER OF DEEDS

1. Public Land Survey T 14N R 08W H-11  
T R  
T R  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

Register of Deeds Stamp & File Number

- 4 Lot No. , Recorded Plat  
5. Private Claims

I, JAMES G. KNAPP, in a field survey on SEPTEMBER 30, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Only one corner may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

DEPUTY SURVEYOR, NOAH BROOKFIELD, SET POST IN JUNE 1839, CORNER POST PLACED 39.88 CHAINS (2632.08 FEET) FROM CORNER COMMON TO SECTIONS 26, 27, 34, AND 35, AND WITNESSED: HEMLOCK 20" EAST 13 LINKS (8.58 FEET)  
MAPLE 18" N44°W 12 LINKS (7.92 FEET)

CORNER CALLED FOR IN COUNTY SURVEYOR'S BOOK NO. 1, PAGE 114, (FROM FIELD BOOK NO. 5, PAGE 154), BY L. W. JUNE, COUNTY SURVEYOR, DATED OCTOBER 8, 1902, AND NOTED AS, "STAKE - EQUAL MEASURE", AND BEING 39.96 CHAINS (2637.36 FEET) FROM N.E. CORNER AND N.W. CORNER, SECTION 34.

CORNER RECORDED AS PER P. A. 74 OF 1970, BY HENRY J. MULDER, P.S. 25862, ON OCT. 28, 1986, IN LIBER 2, PAGE 147, AND NOTED AS, "END. 2" PIPE 1' SOUTH OF E-W GRAV. RD. OPPOSITE STP. FNC. LINE RUNNING SOUTH - HELD FOR CORNER", AND WITNESSED

NORTH 33.63' P.P.  
S5°E 33.30' TEL. P.  
S40°W 135.61' YARD LAMP POLE  
S60°W 107.00' FACE 12" PINE

APPROVED BY MECOSTA CO. PEER GROUP  
IN ACCORDANCE WITH P.A. 345 of 1990

*James G. Knapp*  
CHAIRMAN  
DATE FEB. 13, 1998

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

ON SEPT. 30, 1994, FOUND 1/2" X 18" RE-BAR, (BURIED 3" BELOW ROAD SURFACE), DRIVEN INTO 1-3/4" IRON PIPE, 12" DEEP, IN CENTER OF 7 MILE ROAD (24' GRAVEL) AND IN LINE WITH STUMP FENCE - NORTH.

AFTER BITUMINOUS PAVING IN SUMMER 1995, CORNER IS 1.8' SOUTH OF CENTERLINE 22' BITUMINOUS.

MEASURED DISTANCE TO G-11 = 2636.43', TO I-11 = 2635.12'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H - 11, 1/4 CORNER COMMON TO SECTIONS 27 AND 34, T14N-R08W.  
FOUND 1/2" X 18" RE-BAR, DRIVEN INTO A 1-3/4" IRON PIPE, AND IS ACCEPTED AS A CAREFUL AND FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

REMOVED THE 1/2" X 18" RE-BAR, DRIVEN INTO A 1-3/4" IRON PIPE, AND PLACED IN THE SAME POSITION A STANDARD MECOSTA COUNTY REMONUMENTATION MONUMENT, INSIDE OF A HIGHWAY MONUMENT BOX, AND WITNESSED:

SET 60d SPIKE W/REMONUMENTATION TAG IN EAST SIDE OF 8" BLACK OAK AZ. 184°, 94.02 FEET  
SET 60d SPIKE W/REMONUMENTATION TAG IN S.E. SIDE OF UTILITY POLE AZ. 222°, 135.93 FEET  
SET 60d SPIKE W/REMONUMENTATION TAG IN NORTH SIDE OF 20" WHITE PINE AZ. 243°, 107.33 FEET  
SET 60d SPIKE W/REMONUMENTATION TAG IN EAST SIDE OF UTILITY POLE AZ. 357°, 33.67 FEET



Signed by *James G. Knapp*

Date

JUNE 28, 1999

Surveyor's Michigan License No. 25853

LIBER 101 PAGE 133

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993