## SURVEY & REMONUMENTATION

FEB 2 6 1998

MECOSTA COUNTY REMONUMENTATION PROGRAM

CORNER APPROVED BY PEER GROUP ON 11-14-97

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

SECTION For Corners in

( County)

Located In:		Corpor Code #	
		-	
•			
	-		

STATE OF MICHIGAN COUNTY OF MECOSTA RECEIVED FOR RECORD Corner Code # 15N 9W J-07 T R R DEG 29 AIO :06 R T T R R R

2. Property controling in Section

1. Public Land Survey

Miscellaneous Property in Sec.

5. Private Claims

4. Lot No.

Register of Deeds Stamp & File Number

I, <u>James H. Carter</u>, in a field survey on <u>October 31,1997</u>, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of court law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of Michigan Board of Land Surveyors or by a decree of a court of law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

С D E F G Н J 4-3 12 6 48 117 16 15 -- 14 ---13 7 10 29. 27 25 11 12

NOTE: Only one corner may be recorded on this certificate.

, Recorded Plat

A. Description of original monument and accessories and /or subsequent restoration:

1838 - JAN 29 - FEB 7, DEPUTY SURVEYOR, A. E. VAN NESS, SET POST. TAMARACK 12" - N 6 1/2 E - 9 LINKS, TAMARACK 15" -

S 3 E - 7 LINKS,

1996 - MID MICHIGAN ENGINEERING AND SURVEYING, CERTIFICATE OF SURVEY L 12, P 121, FOUND 3" CLAY TILE & 1/2" IRON ROD.

NAIL IN 36" WHITE OAK - S 31 E - 12.65'FT, NAIL IN 14" WHITE OAK - N 88 W - 18.08' FT, NAIL IN 12" MAPLE - N 32 W -

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD INSIDE CLAY TILE, FOUND NAIL IN 44" OAK - S 20 E - 12.56', FOUND NAIL IN 18" OAK - N 85 W - 17.97' FOUND NAIL IN 18" MAPLE - N 25 W - 7.62', FOUND NAIL IN 30" OAK - N 03 W - 32.36'.

SET MECOSTA COUNTY REMONUMENTATION MONUMENT OVER CLAY TILE

APPROVED BY MECOSTA CO. PEER GROUP IN ACCORDANCE WITH P.A. 245 of 1990 Ma

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-7 - CORNER COMMON TO SECTIONS 14 AND 23, T15N, R09W.
SET A STANDARD MECOSTA COUNTY REMONUMENTATION MONUMENT AND IS ACCEPTED AS A CAREFUL FAITHFUL REESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

S 20 E - 12.56' - NAIL IN 44" OAK N 85 W - 17.97' - NAIL IN 18" OAK N 25 W - 7.62' - NAIL IN 18" MAPLE N 03 W - 32.36' - NAIL IN 30" OAK

Date

CENSED No. 33973 LAND SUP

OF MICHIGAN

JAMES HOWARD CARTER AND SURVEYOR

ME.

Signed by

Surveyor's Michigan License No.