SURVEY & REMONUMENTATION

FEB 2 6 1998

## MECOSTA COUNTY REMONUMENTATION PROGRAM

## CORNER APPROVED BY PEER GROUP ON December 12, 1997

SECTION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN COUNTY OF MECUSTA

For corners in						H.	ECEIVED.	THERE	CURI	
MECOSTA	Located In:	Corne	er Code #	1						
(County)				1		'97	nen 4	<b>7/7</b> a	10.00	
						31	DEU	29 A	W 400	
4 Dublin Land Comme	T 15.*	D 10	7 08							
Public Land Survey	<u>T 15N</u>		<u>L-07</u>	İ		(				
		R				,	erzene Grzene	1/3 <sub>Av</sub>	wani	
		R				v	REGISTER	of ner	in e	
2 Dranadii Cantrallia	***************************************	R		İ			TEO II PER	· - 022	.03	
2. Property Controlling		R								
in Section		R								
3. Miscellaneous		R		Reg	ister c	of Deeds	Stamp	& File	Numb	er
Property in Sec.	ST	R								
4 Lot No, F	Recorded Plat									
5. Private Claims				···	1 A	BCD	E F	GH	IJK	L.
		***************************************			,			-		T:
					1	6 5	4	3	2	1-
					3 —		<del></del>	-		₩.
I, Thomas H. Sage	, i	n a field survey or	November 26,	<u>1997</u> ,	4	7 8		10	11	12
do hereby certify that under	requirements of P.A. 7	4, Michigan P.A.	of 1970, the corner points	mentioned		′   ັ	1	"	''	'-
in lines 1 and 2 above were	e in conformance with	regulations and	rules therefore as requ	ired in the	5					
current manual of survey ins Management or by a decree	of a Court of Law and/	States Departm or that the corner	tent of the Interior, Bures	U of Land	1	18 17	16	15	4	13
above were in conformance	with the rules of the M	fichigan Roard o	f Land Surveyors or by a i	୦, 4	7	<del>.   -                                  </del>				-
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as					в 1	9 20	21	22	23	24
expressed below:	,,,,		, , , , , , , , , , , , , , , , , , , ,		- I '		-;	1	~~	
					۶ 📙				1.5	
					10  3	0 29	28	27	26	25
NOTE: Only one corner	may be recorded o	on this certific	ate.		11	1 1				
					12 3	32	33	34	35	36
<ul> <li>A. Description of original</li> </ul>	al monument and ad	cessories and	or subsequent restora/	tion:	13 L					
G.L.O., Vol#2, Pg. 286	( Amnil	4 4077 ) local	Diaman D0#40205	( les		070 \ 0		201	,,,,,,,,	
At 39.93 Ch. Set Qtr. Sec		a, 1977) Jack Survey: L.10, P	Pierson , PS#19305				erald Gr		F17743	
Pine 20, N65E, 25Lks.							0, Pg. 70		200	
		ar, N49°W, 16.		Sam	ie into	as L.C.I	R.C. L. 0	1, Pg. 3	369	
Hemlock 10, S61E, 11Lks		Dak, N15°E, 39								
		Pine, N83°E, 54								_
( A		Dak S33°E, 42.					eraid Gr		#17741	F
( April 1969 )	Surveys:	Rec'd Survey: L. 11, Pg. 82 Found Iron: 8" Twin Oak, N10°E, 39.31' #1								
George Blass, PS		<b>1978</b> ; L. 10, F		Four						#1
- Reset "T" iron in C/L old trail N. & S. Aug. 12, 1997; L. 12, Pg. 251					10" Red Oak, S30°E, 42.31' <b>#2</b>					
@ double the distance be					10	)" Oak, I	√50°W, 1	16.61	#3	
NW. Cor. & W. 1/16 Cor.			n Nelson, PS#21273							
on N. Line.		C. L.01, Pg.369		( Au			) Henry			5862
6" Poplar, N49°W, 16.66		"T" Iron w/Blas				ec'd Sur	vey: L. 1	11, Pg.	89	
6" W. Oak, N15°E, 39.28'			Twin White Oak, Az10		i Fo	ound "T"	Iron, w/i	Blass T	ag	
4" W. Pine, N83°E, 54.02			)" Red Oak, Az150°. 42				k, N10°E			
6" W. Oak S33°E, 42.25'			Poplar, Az310°, 16.64			)" R. Oa	k, S30°E	, 42.31	<b>#2</b>	
	Set Nai	I & Tag, NW. S	Bide, 6" W. Pine, Az68	', 44.95' <b>#3</b>	6"	W. Pin	e, N68°E	. 44.95	<b>#3</b>	
B. Description of corner	evidence found and	d/or method ap	plied in restoring or re	establishing	corne	r:				
- Found "T" iron 1.5' belov	w ground									
		present, nail m	nissing; #3) Found na	il & "Nelson	" tag:					
#4) Go		id nail overgrov	<b>u</b> , ,							
,										

- Accepted position of the "T" iron as best evidence of the position of corner.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- Replaced "T" iron with Mecosta County Remonumentation Monument. ("T" iron left inside monument)
  - Fnd. Nail, E. Side, 12" Twin White Oak, N10°E, 39.33' #1
  - Set Nail & Remon. Tag, NE. Face, 12" Twin Red Oak, S30°E, 42.31' #2
  - Found Nail & "Nelson" Tag, NW. Face, 14" W. Pine, N68°E, 44.97' #3
  - -Found Nail, S. Face, 10" W. Pine, N83°E, 54.11' #5
- This Monument is accepted as the best available evidence of the position of the corner.

APPROVED BY MECOSTA CO. PEER GROUP IN ACCORDANCE WITH P.A. 345 of 1990 CHAIRMAN DATE

Signed by Thomas H. Sage

Surveyor's Michigan License No.

331 LAND SURVEY

Date December 17, 1997

FORM APPROVED BY MICHIGAN STATE BIGARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983 ADAPTED FOR WORD PROCESSING MARCH, 1983

LIBER 100 PAGE 372

JSS