

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MIDLAND  
(County)

Located In:

Corner Code #

1. Public Land Survey T 13N R 2W E-7  
T R  
T R  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R  
4. Lot No. , Recorded Plat  
5. Private Claims

STATE OF MICHIGAN  
MIDLAND COUNTY  
FILED

19 JUL 95 10:52 A.M.

BEVERLY J THAYER  
Register of Deeds Stamp & File Number

I, PAUL B. LAPHAM, in a field survey on MAY, 19 95  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.**

- A. Description of original monument and accessories and/or subsequent restoration:  
E-7 Corner common to Sections 16, 17, 20 and 21

1852 AUSTIN BURT, OLD CORNER, SUGAR 8" S29°W, 34 LKS., SUGAR 16" N39°E 60 LKS.

1899 COUNTY SURVEY RECORDS. SURVEY OF SECTION 21

SEPT. 22, 1969 HUNTER, WHITTIER & SOLBERG, SURVEY

NOV 16, 1969 HUNTER, WHITTIER & SOLBERG, FIELD NOTES

WITNESS NOTE: Witnesses from above surveys and LCRC's are available in dossier file; which was  
presented to peer review committee and is on file at the Register of Deeds Office.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-7 Corner common to Sections 16, 17, 20 and 21

Found 5/8" sq. bolt in 3/4"x18" pipe, set std Monument 5/8"x18" in Mon. box, Meas. 2649.4' to F-7 per Hunter  
Whittier & Solberg's field notes.

Corner, E-7 was approved for remonumentation at a Peer Review Committee Meeting on June 6, 19 95

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-7 Corner common to Sections 16, 17, 20 and 21

Set 5/8" x 18" re-rod with brass cap stamped "Midland Co. Remon. Cor. PS 9433" in Monument Box per Surveys  
by C.S.R. and Whittier. Accepted as best available evidence of the accepted position of the corner.

N35°W, 59.8' - N&T IN POWER POLE  
N65°E, 46.0' - N&T IN TOP GUARD RAIL POST  
S45°E, 35.4' - N&T IN TOP GUARD RAIL POST  
S70°W, 102.25' - N&T IN TOP GUARD RAIL POST

Signed by

Paul B. Lapham

Date

June 6, 1995

Surveyor's Michigan License No.

9433

