

Land Corner Recordation Certificate
Attachment B to 2016 Annual Grant Agreement
Authority: MCL 54.205 and R54.202

This form is ONLY for corners filed under the 2016 State Survey and Remonumentation Grant Agreement

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2016 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Midland County Edenville Twp.

Corner Type Survey Township Corner Code

Original Public Land Survey Corner

• MCL 54.202(g)

• MCL 54.262(g)

Property Controlling Corner

• MCL 54.202(i)

• MCL 54.262(h)

Protracted Public Land Survey Corner

• MCL 54.202(k)

• MCL 54.262(i)

T		R			1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
T		R			2	6			5		4		3		2		1		2
T		R			3														3
T		R			4	7			8		9		10		11		12		4
					5														5
S	T		R		6	18			17		16		15		14		13		6
S	T		R		7														7
S	T		R		8	19			20		21		22		23		24		8
S	T		R		9														9
					10	30			29		28		27		26		25		10
T	16N	R	1W	F1	11														11
T		R			12	31			32		33		34		35		36		12
T		R			13														13

Part A: Corner(s) History

F1 - None

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner(s)

F1 – ¼ Corner on North line of Section 4, T16N, R1W – No evidence of corner found. Set stamped 4" DNR Aluminum Cap on 1" x 36" long iron pipe midway between closing corners 'E1' and 'G1' on standard line. Distance West to 'E1' is 2680.56' and distance east is 2680.55' to 'G1'. DNR Monument accepted as the best available evidence of the position of the corner.

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

F1 – Stamped 4" DNR Aluminum Cap on 1" x 36" long galvanized iron pipe. Set Blue Carsonite Post 1' South  
S42°E 23.28' to set Nail & Tag (N & T) in NE side 3" Red Maple  
S46°W 39.82' to set N & T in NW side 3" Red Maple  
N67°W 41.51' to set N & T in S side 8" Cherry  
N61°W 16.89' to set N & T in NE side Tw. 3" & 6" Red Maple scribed 'XBT'  
West 1.65' to 'F13' T17N, R1W – DNR Monument  
S70°53'E 12.15' to Fd. ½" CIR # 14759

Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
March 28, 2016	N43°48'51.0515"	W84°26'12.1521"	NAD83 (2011)	2010

Set Direct using RTK and position verified by 2 static GNSS Baselines from Local OPUS Base stations.

I, Craig W. McVean, in a field survey on March 28, 2016, certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL 54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

Craig W. McVean12/7/2016

Craig W. McVeanDate

Professional Surveyor's License No.: 39088

Michigan Department of Natural Resources, 8015 Mackinaw Trail, Cadillac, MI



I, Brian D. Ferguson, state that the corner(s) identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on Aug. 3, 2016, and is accepted for filing in the Midland County Remonumentation Program.

Brian D. FergusonDate

Professional Surveyor's License No.: 26454