

Land Corner Recordation Certificate
Attachment B to 2016 Annual Grant Agreement
Authority: MCL 54.205 and R54.202

This form is ONLY for corners filed under the 2016 State Survey and Remonumentation Grant Agreement

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2016 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Midland County Edenville Township

Corner Type Survey Township Corner Code

Original Public Land Survey Corner T 16N R 1W C8

Property Controlling Corner S T R

Protracted Public Land Survey Corner T R

Grid: 13x13 with columns A-M and rows 1-13. Corner 20 is marked with a dot.

Part A: Corner(s) History

- C8 – 1832 – GLO – H. Parke – Set 1/2 mile post.
1) Maple 14" S64°E 19 L.
2) Maple 10" N64°W 21 L.
- 1852 – GLO – Resurvey – A. Burt – Old government corner, set post.
3) W. Pine 12" S28°W 35 L.
4) Maple 12" N37°E 24 L.
- 1901 – CSR – L. 1, p. 92 – F. J. Gibbs – Old corner, post standing – Sec. 19 Petition Survey.
3) Pine stump S28°W 35 OB
5) Pine stub 20" S35°E NB

Part B: Surveyor’s Report on Perpetuation or Monumentation of Corner(s)

C8 – ¼ Corner common to Section 19 and 20, T16N, R1W – Found remains of witnesses #3 & #5, dug 2’ x 3’ area, wet sand but no conclusive evidence of wood post was found. Set stamped 4” DNR aluminum cap on 1” x 36” galvanized pipe from the pine stump BT’s. Also fits GLO White Pine Line Tree stump to the south. S0°40’05”W 601.22’ (Grid) [603.24’ - 20” W. Pine – GLO] to set 2” Alum. Cap on 5/8” x 34” rebar in centerline remains 20” WPS. DNR Monument accepted as a careful and faithful perpetuation of the position of the original corner.

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

C8 – Stamped 4” DNR aluminum cap on 1” x 36” galvanized iron pipe.
N50°E 7.32’ to set nail & tag in SE side of 7” Oak scribed ‘XBT’
S03°W 28.38’ to set nail & tag in W. side of 11” R. Maple scribed ‘XBT’
S60°W 24.95’ to set nail & tag in NW side of 9” R. Maple scribed ‘XBT’
N70°W 15.88’ to set nail & tag in N. side of 10” Oak scribed ‘XBT’
Set Blue Composite Post 1’ W.

| Date of Observation | Latitude | Longitude | Datum and Adjustment Year | Epoch Date |
|---------------------|-----------------|-----------------|---------------------------|------------|
| May 21, 2015 | N43°45’47.9208” | W84°28’02.5013” | NAD83 (2011) | 2010 |

Position determined from Static GNSS Baselines from 2 Local OPUS Base stations adjusted by Least Squares

I, Craig W. McVean, in a field survey on May 21, 2015, certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL 54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

Craig W. McVean

Craig W. McVean

Professional Surveyor’s License No.: 39088

Department of Natural Resources, 8015 Mackinaw Trail, Cadillac, MI 49601

12/7/2016

Date



I, Brian D. Ferguson, state that the corner(s) identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on Aug. 3, 2016 and is accepted for filing in the Midland County Remonumentation Program.

Brian D. Ferguson

Brian D. Ferguson

Professional Surveyor's License No.: 26454

Date