Land Corner Recordation Certificate

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Craig W. McVean Field Survey Date: Oct. 2016 For corner(s) in: Midland County **Original Public Land Survey Corner Corner Code** S Т R Т S R Т R S Т R **Property Controlling Corner Corner Code** S R 5 5 Т S R - 18 -6 Т R S 7 R S 19 20 24 8 **Property Corner Corner Code** 9 9 30 T 16N **1W** S R 5 10 29 10 T 16N S R **1W** 11 11 Т R S 12 31 32 33 35 36 12 S 13 ABC DE **Protracted Public Land Survey Corner Corner Code** Т R S Т R S T R

Part A: Corner History

5 - CN 1/16 Cor. Section 30, T16N, R1W 1908 - CSR L. 1, p. 253 - F. **T**. Gibbs Set Gas pipe for corner

- 1) Pine stp. N24°W 27
- 2) Pine stp. S4°W 16

<u>6</u> –NE 1/16 Cor. Sec. 30, T16N, R1W - None

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

- 5 CN 1/16 Corner Sec. 30, T16N, R1W Could not find any conclusive evidence of Gibb's gas pipe or witnesses. Excavated along 10' of E-W Fence searching for pipe but must have been removed during construction of fence. Fence is old barb wire on ground and newer wolven wire still standing. Thus set stamped 2" Aluminum Cap on 5/8" x 34" long iron rebar per Standard BLM procedure. Falls in said E-W fence. Found trace of fence to the North in 24" WPS 67' North.
- 6 NE 1/16 Corner Sec. 30, T16N, R1W No evidence of monument. Set 2" Alum. Cap on 5/8" x 34" rebar per standard BLM procedure. Corner of wolven wire fence W & S is 2.5'± N & 9'± E. Corner falls on E. side of elevated deer blind.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

5 - CN 1/16 corner Sec. 30, T16N, R1W - Stamped 2" Aluminum Cap on 5/8" x 34" long iron rebar. Set Blue Composite Post with loc. tag 1' N. N57°E 11.29' to set N & T in N. side 7' W. Oak N19°E 41.34' to set N & T in W. side 13" Red Maple N36°W 60.44' to set N & T in SW side 12" Red Maple.

N78°W 55.01' to set N & T in N. side Tw. 17" & 26" Oak.

6 - NE 1/16 Corner Sec. 30, T16N, R1W - Stamped 2" Aluminum cap on 5/8" x 34" long iron rebar. Set Blue Composite Post with loc. tag 1' NE N87°E 6.09' to set N & T in S. side 15" Oak N46°E 25.45' to set N & T in NW side 9" R. Maple N03°W 18.42' to set N & T in S. side 7" R. Maple S65°W 46.97' to set N & T in N. side 8" Oak



Craig W. McVean

Date

Professional Surveyor's License No.:

39088

Prepared By: Craig W. McVean Michigan Dept. of Natural Resources 8015 Mackinaw Trail Cadillac, Michigan 49601