

**REMON CORNER A-6, EDENVILLE TWP.
LAND CORNER RECORDATION CERTIFICATE**
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Midland
(County)

Located in: Corner Code #

1. Public Land Survey

T 16N R 1W A-6

T R

T R

T R

2. Property Controlling
in Section

S T R SURVEY &
S T R REMONUMENTATION

3. Miscellaneous
Property in Sec.

S T R

S T R FEB 23 2001

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____ SECTION _____

534

STATE OF MICHIGAN
MIDLAND COUNTY
REMONUMENTATION & FILED

12/28/2000 8:44:27 AM

SCOTT I. HAINES
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, **RODNEY CLAYPOOL**, in a field survey on June 11, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned on lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-6 1/4 Corner for Section 18 on West townline

Not set by Glo
No record of being set or found.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-6 1/4 Corner for Section 18 on West townline

Set 5/8" rod and cap at midpoint between A-5 and A-7 on controlling Township line between M-6 and M-7 Warren Twp., T16N-R2W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-6 1/4 Corner for Section 18 on West townline

Set 5/8" rod and brass cap stamped Midland Co. Remon Cor. PS 29241 and is accepted as the best available evidence of the position of the accepted corner.

N 83 Deg E, 57.54', nail in fence post
S 60 Deg E, 60.71', nail in 6" Ash
N 42 Deg W, 58.98', chiseled "+" in concrete pipe
N 64 Deg W, 44.12', chiseled "+" in concrete pipe
North 8.25', Warren Twp. corner M-6
East 4.8', centerline M-18

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Signed by Rodney D. Claypool
Surveyor's Michigan License No. 29241

Date 12-28-00
Form approved by Michigan State Board of Land Surveyors, Jan. 28, 1971
Revised May 14, 1971
Revised Jan., 1983

