

For corners in Midland

Located in: **Comer Code #**

1. Public Land Survey

T 16N R 1W A-8

T R

T R _____

TR SURVEY &

2. Property Controlling in Section

S T R ~~REMONUMENTATION~~

S T R

3. Miscellaneous

S T R FEB 09 2004

Property in Sec.

S T R FEB 23 2001

4. Lot No. . Recorded Plat SECTION

5. Private Claims

I, RODNEY CLAYPOOL, in a field survey on June 23, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned on lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-8 ¼ Corner for Section 19 on West townline

Not set by Glo

Survey by F. Gibbs, 1901, set gas pipe at midpoint on line

Survey by MDOT, 1937, corner not found

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-8 ¼ Corner for Section 19 on West townline

Set 5/8" rod and brass cap at midpoint between A-7 and A-9 on Controlling Townline between M-7 and M-9, T16N-R2W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8 ¼ Corner for Section 19 on West townline

Set 5/8" rod and brass cap stamped Midland Co. Remon Cor. PS 29241 in monument box and is accepted as the best available evidence of the position of the accepted corner.

S 70 Deg W, 54.81', nail and plastic disk in 15" Ash clump

S 30 Deg W, 92.50', nail and plastic disk in 18" Ash

S 30 Deg E, 85.72', nail and plastic disk in power pole

N 30 Deg E, 88.63', nail and plastic disk in 5" Ash

North 2' \pm , tree line to East

East 0.5', centerline M-18

South 12.09', Warren Twp. corner M-8

Signed by Shodney D
Surveyor's Michigan License No. 29241

Date 12-26-00

Form approved by Michigan State Board of Land Surveyors, Jan. 28, 1971

Revised May 14, 1971

Revised Jan., 1983

