REMON CORNER A-1, EDENVILLE TWP. REMON CORNER M-1, WARREN TWP. LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Comer Code #

Located in:

T 16N R 1W

For corners in

(County)

corner.

S 50 Deg W, 73.20', pk nail in power pole N 45 Deg E, 63.30', nail in power pole N 45 Deg W, 51.90', centerline West end 48' CMP N 35 Deg E, 55.15', Westerly corner concrete project marker

Midland

529

STATE OF MICHIGAN

HIDLAND COUNTY

REMONUMENTATION & FILED

	1. Public	Land Survey	T 16N R 2W SURWAY 8 M-1	12/28/2000 8:44:27 AM
			T RESMONUMENTATION	SCOTT I. HAINES
			· ·	REGISTER OF DEEDS
	2. Prope	ty Controlling S	T-R- FEB-23 2001	VEGIGIEV OF PETER
	in Sec	tion 3	T_R	and the same & File Number
	3. Misce	laneous S	T R SECTION	Register of Deeds Stamp & File Number
	Prope	rty in Sec. S		
		Decorded Plat		A B C D E F G H I J K L M
	4. Lot N	, Recorded Plat		♦ • • • • • • • • • • • • • • • • • • •
	5. Privat	e Claims		2 + 6 + 7 + 4 + 7 T 1 1 1 1
	, DODNE	CLAYPOOL, in a field survey on AM	il 3, 1999, do hereby certify	3
			1 7 + 8 + 9 + 10 + 11 + 12	
	lines 1 and	2 above were in control instructions of	the United States Department of the	5 15 15 14 13
				6 - 18 + 17 + 16 + 15 + 14 + 13]
	corner po	IUR Wellington III III III and a print	necree of a Court of Law, re-established	,
	of the Mic	nigan Board of Land Surveyors of by a ted, re-monumented, recovered, foun	d as expressed below:	3 + 19 + 20 + 21 + 22 + 23 + 24
	Monane	ted to the test of	the same town and range, may be	<u> </u>
	NOTE:	Not more than 2 corners, all in	the same town and range, may be	$\frac{10}{10}$ $\frac{1}{30}$ $\frac{1}{29}$ $\frac{1}{28}$ $\frac{1}{27}$ $\frac{26}{25}$ $\frac{25}{25}$
	,	recorded on this certificate.		"
				$\frac{11}{12}$ $+ \frac{31}{31}$ $+ \frac{32}{32}$ $+ \frac{33}{33}$ $+ \frac{34}{35}$ $+ \frac{35}{35}$ $+ \frac{36}{35}$
				13
	4 5.0	winting of original monument and	accessories and/or subsequent restoration:	·
	A. Des	cupuon or original more	accessifies and of our of the first section 31	T17N-R1W and Section 36, T17N-R2W
	A-1	Corner common to Section 6, T	16M-K IAA' Section I' Light I	
		- C by I Knoy 1913. 3X3 5	Cedar 2 1/2' above ground	HODREY D. CLAYPOOL
ľ		Survey by MDOT, 1942, found	corner	∰ ± 1 1,860 €*3
		Survey by M. Hunter, witness C	4 16" rod in monument box	MINUTE OF THE STATE OF THE STAT
		Survey by J. Jones, 1995, Iddit	4" iron in monument box	700
		I ADA NI I INNAS 1997. IUUIIV	72 100 11	
		Gladwin County Remon LCRC	#359	
ı	*			
ı	Survey by M. Hallet, 1995, found ½ rod in monument box Survey by J. Jones, 1995, found ½ rod in monument box LCRC by J. Wilcox, 1981, found 1" iron in monument box LCRC by J. Jones, 1992, found ½ rod in monument box Gladwin County Remon LCRC #359 B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.			
ı	B. Description of corner evidence found and/of method applies with the A-1 Corner common to Section 6, T16N-R1W; Section 1, T16N-R2W; Section 3			4 T17N-R1W and Section 36, T17N-R2W
	A 4	Corner common to Section 6,	r16N-R1W; Section 1, T16N-R2W; Section 3	
Н	A-1	Corner common to Section 6, T16N-R1W; Section 1, 110N-R1W, December 1, 110N-R1W; Section 1, 1		
:		Found 1/2" rod in monument bo	x at a position per surveys and	
			•	
		•	and accessories established to perpetuate le	ocating the position of the corner:
ı	C. D	escription of monument for corner	and accessories established to be be a	- TITLE DAW and Section 36, T17N-R2W
			- TANLEY SECTION 1 TANLEY AV SECTION	J (, 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ı	A-1	Corner common to Section o,	the second is another as	the best available evidence of the position of the origin
		Found Gladwin County Remo	on Cap in monument box and is accepted as	**************************************

12.26-00 Form approved by Michigan State Board of Land Surveyors, Jan. 28, 1971 Revised May 14, 1971 Revised Jan., 1983 Date Signed by Arthur D. Surveyor's Michigan License No. 29241

> J.P. HOYED LAND COR. L.A P.A. 345 OF 1990 MIDLAND COUNTY