SURVEY & REMONUMENTATION

FEB 1 3 1998

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A., 1970

MONSCE 158) Located In: Comer Cinde 8 Ash Twp. 1. Public Land Survey 1. S.R. R.B. R. R.B. R. R. R. R.B. R. R. R.B. R. R. R. R. R.B. R. R	For corners in SECTION	Filing Require	ment of Act 74, Mich. P.A., 19	970 S 70	
3. Miscellaneous S R R Property in Sec. R Property in Sec. R S. Private Claims 1. George B. Wantks. Jr. in a field survey on Oobbor — December, 1937 do heekly defin that where conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the current patients marrial of survey infatuctions of the current patients marrial of survey infatuctions of the current patients and recovered, found as experience of a Court of the Courter patients marrial of survey infatuctions of the current patients and recovered to the current patients of the Michigan of the Courter patients marrial of survey infatuctions of the Courter patients marrial of survey infatuctions of the Michigan of the Courter patients and the current patients of the Michigan of the Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Courter patients of the Cour		Located In:	Corner Code #	T DE	
3. Miscellaneous S R R Property in Sec. R Property in Sec. R S. Private Claims 1. George B. Wantks. Jr. in a field survey on Oobbor — December, 1937 do heekly defin that where conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the conformance with regulations and rates therefore as equited in the current marrial of survey infatuctions of the current patients marrial of survey infatuctions of the current patients marrial of survey infatuctions of the current patients and recovered, found as experience of a Court of the Courter patients marrial of survey infatuctions of the current patients and recovered to the current patients of the Michigan of the Courter patients marrial of survey infatuctions of the Courter patients marrial of survey infatuctions of the Michigan of the Courter patients and the current patients of the Michigan of the Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Michigan Courter patients of the Michigan Courter patients and the current patients of the Michigan Courter patients and the current patients of the Courter patients of the Cour		T <u>5S</u> R <u>9E</u> TR_ TR		VED FOR RECOGNITY, M	
4. Lot No. Recorded Plat 5. Private Clar ms Cascer B. Winnies Jr. In a feet earway on Debtor December 1997 th interby stein find under recattements of P.A. 74. Millipan P.A. of 1977 (the contral politic mechanisms in mark 12 above when in conformation with the professor as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and / or with the corner points mericioned in line 3, 4 and 5 above were in conformance with with the corner points mericioned in line 3, 4 and 5 above were in conformance with with the current professor and or survey instructions of the United States Department of the Interior States Department of Interi	in Section 3. Miscellaneous	STR STR		U	
I. Gerote B. Wimike. Jr. In a field survey on October - December 1997 do hereby state that under requirements of P.A. 74. Markipan P.A. of 1970, the corner points meritioned in lines 1 and 2 above were in conformance with regulations and tree therefore are required in the current instructions of the text the corner points meritioned in lines 3,4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors of by a Decree of a Coust of Law, established, re-setablished, monumental, recovered, found as expressed below. NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. A. Decaription of original monument and accessories and/or subsequent restoration: 1817, GLO Surveyor, Joseph Fielcher set the post corner of Sections 9, 10, 15, 8, 16, 11, 11, 11, 11, 11, 11, 11, 11, 11					
recultements of P.A. 74, Michigan 2.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and fuse therefore as regular in the corner points regulated in the corner point in the corner point in regulation and the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in equipment of the first point in the corner point in the same fown and range, may be recorded on this certificate. 1997 REMONUMENTATION PROGRAM CORNER A Cescription of original monument and accessories and/or subsequent restoration: 1617, GLO Surveyor, Joseph Fletcher set the post corner of Sections 9, 10, 15, 8-16, 10 mon which as W. Cask 20 in dia bears N 89 W 15 kes, and an Elm 10 in dis bears N 29 E 26 liss 1878, Ferd Suckely shows found stone — no witnesses 1994, AJ Marino survey shows found work found in pulp — no witnesses 1995, AJ Marino notes shows f. cross — witnesses: SE 36.7 Edison pole / SW 33 24* maple Case & Fleck survey shows corner but does not state what was sound 1997, AJ Marino survey shows corner but does not state what was sound 1997, AJ Marino survey shows corner but does not state what was sound 1997, AJ Marino survey shows corner but does not state what was sound 1997, AJ Marino survey shows corner but does not state what was sound 1997, No. 1998, No. 1999, N	5. Private Claims			A B C D E F G H I J K L	
1997 REMONUMENTATION PROGRAM CORNER A Description of original monument and accessories and/or subsequent restoration: 1817, GLO Surveyor, Joseph Fietcher set the post corner of Sections 9, 10, 15, 8, 16, from which a W. Clask 20 in. dia bears N 89 W 15 liks, and an Elm 10 in. dia bears N 29 E2 bils a 1878, Fred Buckley shows found stone – no witnesses 1496, A.I Marino survey shows rod in conc. – no witnesses 1495, A.I Marino survey shows rod in conc. – no witnesses 1495, A.I Marino survey and notes show found fron plug – no witnesses 1495, A.I Marino survey and notes show found ton plug – no witnesses 1495, A.I Marino survey and notes show found state what was found 1997, A.I Marino survey and notes show F. PK nail – witnesses: S 65.6° bill pole / SW 33 '24" maple Case & Fleck survey shows corner but does not state what was found 1997, A.I Marino survey and notes show F. PK nail – witnesses: S 65.6° bill pole / NE 24.16' nail P pole / SW 33.38' nail 30' tree 1970, Ervin P Miller (Michigan Dept. of State Highways and Transportation) survey (Liber 725, Page 112) and LCRC (Liber 2, Page 1970, Ervin P Miller (Michigan Dept. of State Highways and Transportation) survey (Liber 725, Page 112) and LCRC (Liber 2, Page 1970, Ervin P Miller (Michigan Dept. of State Highways and Transportation) survey (Liber 725, Page 112) and LCRC (Liber 2, Page 1970, B.B. Warnke crew found and/or method applied in restoring or re-establishing corner: 10/7/1997, G.B. Warnke crew found and/or method applied in restoring or re-establishing corner: 10/7/1997, G.B. Warnke crew found apped (#16034 – George Avendt, Jr.) *T" iron in existing monument box in concrete pavement for Carreton Rockwood Road RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 10/14/1997, COUNTY REP. 12/1997, G.B. Warnke crew attempted to set 1* x 30* iron pipe with no success. Reset "T" iron with set yellow plastic remonumentation cap under found existing cope #16034 on found "T" iron in existing monument box and is accepted as the best available	requirements of P.A. 74, Michigan P.A. conformance with regulations and rules the United States Department of the Interior, that the corner points mentioned in lines Board of Land Surveyors or by a Dec	of 1970, the corner points mei herefore as required in the curre Bureau of Land Management of 3, 4 and 5 above were in confi	ntioned in lines 1 and 2 above were in ent manual of survey instructions of the or by decree of a Court of Law and / or ormance with the rules of the Michigan	3 4 7 8 9 10 11 12 5	
1997 REMONUMENTATION PROGRAM CORNER A. Description of original monument and accessories and/or subsequent restoration: 1817, GLO Surveyor, Joseph Fietcher's et the post corner of Sections 9, 10, 15, 8, 16, from which a W. Oak 20 in dia bears N 89 W 15 lks, and an Elm 10 in. dia bears N 29 E 28 lks 1878, Fred Buckley shows found stone – no witnesses 1960, AJ Marino survey and notes show found fron plug – no witnesses 1962, AJ Marino survey and notes show found fron plug – no witnesses 1962, AJ Marino survey and notes show found fron plug – no witnesses: 1967, EA, Marino survey and notes show found stone what was found 1967, AJ Marino survey and notes show found fron plug – no witnesses: 1969, AJ Marino survey and notes show found fron plug – no witnesses: 1969, AJ Marino survey and notes show found fron plug – no witnesses: 1969, AJ Marino survey and notes show found fron plug – no witnesses: 1969, AJ Marino survey and notes show found fron plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1969, AJ Marino survey and notes show for plug – no witnesses: 1960, AJ Marino survey and notes s	NOTE: Not more than 2 corners, all	in the same town and range,	may be recorded on this certificate.		
18.17, GLO Surveyor, Joseph Fletcher set the post corner of Sections 9, 10, 15, 8, 16, from which a W Oak 20 in. dia bears N 89 W 15 lks, and an Elm 10 in. dia bears N 29 E 28 lks 1878, Fred Buckley shows found stone – no witnesses 1960, AJ Marino survey and notes show found iron plug – no witnesses 1960, AJ Marino survey and notes show forces. — no witnesses 1960, AJ Marino survey and notes show forces. — witnesses: SE 36.7 Edison pole / SW 33 '24' maple Case & Fleck survey shows corner but does not state what was found 1967, AJ Marino survey and notes show F. PK nail — witnesses: SE 36.6'3' nail P pole / NE 24.15' nail P pole / SW 33.38' nail 30' tree 1976, Evin P Miller (Michigan Dept. of State Highways and Transportation) survey (Liber 725, Page 112) and LCRC (Liber 2, Page 154) note found boat spike in monument box — witnesses: S 65° W 39.38' SE railing boit on east end of bridge / N 70' 59.86' NE railing boit on east end of bridge B. Description of corner avidence found and/or method applied in restoring or re-establishing corner: 107/1997, CB. Warnke crew found capped (#16034 — George Avendt, Jr.) "T" tron in existing monument box in concrete pavement for Carleton Rockwood Road RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 10/14/1997, COUNTY REP. 12/1997, G.B. Warnke crew attempted to set 1" x 36" iron pipe with no success. Reset "T" iron with set yellow plastic remonumentation cap under existing cap #16034 in existing monument box. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set yellow plastic remonumentation cap under found existing gap #16034 on found "T" iron in existing monument box and is accepted at the best available evidence of this position of the original corner. Witnesses. South 55' West 39.12 feet to southeast railing bott on east end of bridge Noth 19474 WARNING, JA APPROVED BY MICHIGAN STATE BOARDO FLAND SINGELY BLAND BRYEND MAY TALL BOARDO FLAND SINGELY BLAND BRYEND MAY TALL B	1997 REMONUMENTATION PRO	GRAM CORNER			
10/7/1997, G.B. Warnke crew found capped (#16034 – George Avendt, Jr.) "T" iron in existing monument box in concrete pavement for Carleton Rockwood Road RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 10/14/1997, COUNTY REP. 12/1997, G.B. Warnke crew attempted to set 1" x 36" iron pipe with no success. Reset "T" iron with set yellow plastic remonumentation cap under existing cap #16034 in existing monument box. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set yellow plastic remonumentation cap under found existing cap #16034 on found "T" iron in existing monument box and is accepted as the best available evidence of the position of the original corner. Witnesses: South 55° West 39 12 feet to southeast railing bolt on east end of bridge North 70° West 59, 51 feet to northeast railing bolt on east end of bridge South 20° West 22.90 feet to southeast end of curb for east side of bridge North 45° West 37.35 feet to northeast end of curb for east side of bridge Signed by Signed by Signed by 19474 WARNINE, JR. WARNING, JR. WARNING, JR. WARNING,	1817, GLO Surveyor, Joseph Fletcher set the post corner of Sections 9, 10, 15, & 16, from which a W. Oak 20 in. dia bears N 89 W 15 lks, and an Elm 10 in. dia bears N 29 E 28 lks 1878, Fred Buckley shows found stone – no witnesses 1946, AJ Marino survey shows rod in conc. – no witnesses 1950, AJ Marino notes show found iron plug – no witnesses 1952, AJ Marino notes shows f. cross – witnesses: SE 36.7' Edison pole / SW 33' 24" maple Case & Fleck survey shows corner but does not state what was found 1967, AJ Marino survey and notes show F. PK nail – witnesses: SE 36.63' nail P pole / NE 24.15' nail P pole / SW 33.38' nail 30" tree 1976, Ervin P Miller (Michigan Dept. of State Highways and Transportation) survey (Liber 725, Page 112) and LCRC (Liber 2, Page 154) note found boat spike in monument box – witnesses: S 55° W 39.38' SE railing bolt on east end of bridge / N 70° '				
12/1997, G.B. Warnke crew attempted to set 1" x 36" iron pipe with no success. Reset "T" iron with set yellow plastic remonumentation cap under existing cap #16034 in existing monument box. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set yellow plastic remonumentation cap under found existing cap #16034 on found "T" iron in existing monument box and is accepted as the best available evidence of the position of the original corner. Witnesses: South 55° West 39. 12 feet to southeast railing bolt on east end of bridge South 20° West 59.51 feet to northeast railing bolt on east end of bridge South 20° West 22.90 feet to southeast end of curb for east side of bridge North 45° West 37.35 feet to northeast end of curb for east side of bridge Signed by Signed by Signed by Signed by WARNKE, JR. WARNE, JR. WARNKE, JR. WARNKE, JR. WARNKE, JR. WARNKE, JR. WARNE, JR. WARNKE, JR. WARNKE, JR. WARNE,	10/7/1997, G.B. Warnke crew found capped (#16034 – George Avendt, Jr.) "T" iron in existing monument box in concrete pavement for				
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Set yellow plastic remonumentation cap under found existing cap #16034 on found "T" iron in existing monument box and is accepted as the best available evidence of the position of the original corner. Witnesses: South 55° West 39 12 feet to southeast railing bolt on east end of bridge North 70° West 59.51 feet to northeast railing bolt on east end of bridge South 20° West 22.90 feet to southeast end of curb for east side of bridge North 45° West 37.35 feet to northeast end of curb for east side of bridge Signed by No. 19474 Signed by Sign	RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 10/14/1997, COUNTY REP.				
Set yellow plastic remonumentation cap under found existing cap #16034 on found "T" iron in existing monument box and is accepted as the best available evidence of the position of the original corner. Witnesses: South 55° West 39.12 feet to southeast railing bolt on east end of bridge North 70° West 59.51 feet to northeast railing bolt on east end of bridge South 20° West 22.90 feet to southeast end of curb for east side of bridge North 45° West 37.35 feet to northeast end of curb for east side of bridge Signed by Signed by Surveyor's Michigan License No. 19474 WARNKE, JR. PROFESSIONAL SURVEYOR No. 19474 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19 REVISED MAN, 16, 19					
Signed by Surveyor's Michigan License No. 19474 WARNKE, JR. PROFESSIONAL SURVEYOR No. 19474 PROFESSIONAL No. 19474 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19 REVISED MAY 14, 18 REVISED JAN., 16	Set yellow plastic remonument the best available evidence of t South 55° West 39.12 feet to s North 70° West 59.51 feet to n South 20° West 22.90 feet to s	ation cap under found exis the position of the original o outheast railing bolt on eas ortheast railing bolt on eas outheast end of curb for ea	ting cap #16034 on found "T" iron corner. Witnesses: st end of bridge t end of bridge ast side of bridge st side of bridge		
WARNKE, JR. PROFESSIONAL * SURVEYOR S NO. 19474 SIRVING APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 19 REVISED MAY 14, 19 REVISED JAN., 19	Signed by			Date December 16, 1997	
REVISED OCT 19	Surveyor's Michigan License No		GEORGE B. * WARNKE, JR. * PROFESSIONAL * SURVEYOR No. 19474 FORM APPROVED D	BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 15 REVISED MAY 14, 15 REVISED JAN., 16 REVISED OCT., 15	