LAND CORNER RECORDATION CERTS: CATE County Rep.: 5 Filing Requirement of Act 74, Mich. P.A. 1970	
County Rep.: AX 5000 Filling Requirement of Act 74 Mich D.A. 1970	<b>2</b> 8
For corners in	
Monroe (58) Located In: Corner Code ##	H28 15 10
(County)	
1. Public Land Survey T R	
DUNDEE Typ. T_6S_R_6EM-4	
T R	
T—R—— SURVEY&	କ"େ ୧୦
2. Property Controlling S T R REMONUMENTATION S T R REMONUMENTATION	
	gister of Deeds Stamp & File Number
Property in Sec. S I H APR 0 4 1996 L	
4. Lot No, Recorded PlatCOMMISSION	- A B C D E F G H I J K L
5. Private Claims	
	2 6 5 4 3 2 4 1
1995 REMONUMENTATION PROGRAM	3 + + + + + + + + + + + + + + + + + + +
O D MADNITH TO	* - 7 - + - 8 - + - 9 - + - 10 - + - 11 - + - 1
G.B. WARNKE, JR. in a field survey on Nov.—Dec. 1995 19 19 19 19 19 19 19 19 19 19 19 19 19	5
n lines 1 and 2 above were in conformance with regulations and rules therefore as required in the	6 -18 -17 -16 -15 -14 -1
current manual of survey instructions of the United States Department of the Interior, Bureau of Land	· * <del>             </del>
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a	8 -19 -20 -21 -22 -23 -2
Court of Law; established, re-established, monumented, re-monumented, recovered, found as	9
expressed below:	10 30 29 28 27 26 2!
IOTE: Not more than 4 corners, all in the same town and range, may be recorded	·· <del>·</del>
on this certificate.	12 31 32 34 35 36
A. Description of original monument and accessories and/or subsequent restoration:	13
to Lafler Road compares to Case & Fleck measurement in 70's. 1963 & undated field NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983 (C.B. Warnko (#83-420-4)) FD. 1983	19724 notes corner but not
	19724 notes corner but not RON PIPE. 1. 1991, G.B. Warnke tone) using Detroit Edison
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around spotes)	19724 notes corner but not RON PIPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron, 11/28/95 - corner approved by Feer	19724 notes corner but not RON PIPE.  2. 1991, G.B. Warnke tone) using Detroit Edison corner.  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron, 11/28/95 - corner approved by Feer	19724 notes corner but not RON PIPE.  1991, G.B. Warnke tone) using Detroit Edison corner.  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron, 11/28/95 - corner approved by Feer	19724 notes corner but not RON PIPE.  1991, G.B. Warnke tone) using Detroit Edison corner.  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron, 11/28/95 - corner approved by Feer	19724 notes corner but not RON PIPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron, 11/28/95 - corner approved by Feer	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T65, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 — set hown below.
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Peer brass remonumentation cap in previously set 1" x 36" iron pipe and witnessed as significant forms of the original corner and witnesses.	19724 notes corner but not RON PIPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set hown below.
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Peer brass remonumentation cap in previously set 1" x 36" iron pipe and witnessed as significant productions. 11/28/95 iron pi	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group, 12/7/95 - set hown below.  The position of the corner:  available evidence of long available eviden
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P 1983, G.B. Warnke (#83-420-A) FD. II History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Feer brass remonumentation cap in previously set 1" x 36" iron pipe and witnessed as simple stone of the original corner and witnesses:  Found 3/4" iron pipe being 3.6 feet north & 4.9 feet west - measured 6.95 west +/- 438.5 feet to centerline of Dundee - Azalia Road South 88° 35' East 2550.12 feet to found 3/4" iron pipe for center. Sec. 7, T6S, R South 20° West 19.50 feet to nail/shiner in easterly face of electric pole	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set hown below.  The position of the corner:  available evidence of long and crossing sign?  AMD SURVEYOR NO.
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P 1983, G.B. Warnke (#83-420-A) FD. If History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.)  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Peer brass remonumentation cap in previously set 1" x 36" iron pipe and witnessed as simple stones are supposed to the original corner and witnesses:  Found 3/4" iron pipe with brass remonumentation cap and is accepted as the best the position of the original corner and witnesses:  Found 3/4" iron pipe being 3.6 feet north & 4.9 feet west - measured 6.95  West +- 438.5 feet to centerline of Dundee - Azalia Road  South 88° 35' East 2550.12 feet to found 3/4" iron pipe for center. Sec. 7, T6S, R  South 20° West 19.50 feet to nail/shiner in easterly face of guy pole  North 25° West 34.67 feet to northwesterly face of northerly metal post for railron for the stone same provided and post for railroness and post for	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set hown below.  The position of the corner:  available evidence of long and crossing sign.  The (B-4)  GEORGE B.  WARNAG. IF LAND SURVEYOU NO. 19474
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P 1983, G.B. Warnke (#83-420-A) FD. If History for A-4, T6S, R7E, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.)  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s R7E). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Peer brass remonumentation cap in previously set 1" x 36" iron pipe and witnessed as simple stones are supposed to the original corner and witnesses:  Found 3/4" iron pipe with brass remonumentation cap and is accepted as the best the position of the original corner and witnesses:  Found 3/4" iron pipe being 3.6 feet north & 4.9 feet west - measured 6.95  West +- 438.5 feet to centerline of Dundee - Azalia Road  South 88° 35' East 2550.12 feet to found 3/4" iron pipe for center. Sec. 7, T6S, R  South 20° West 19.50 feet to nail/shiner in easterly face of guy pole  North 25° West 34.67 feet to northwesterly face of northerly metal post for railron for the stone same provided and post for railroness and post for	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set hown below.  The position of the corner:  available evidence of long and crossing sign?  AMD SURVEYOR NO.
NAIL. 1976, Case & Fleck survey #19511 notes S.I.P. 1977, Case & Fleck survey # material but uses same witnesses for S.I.P. 1983, G.B. Warnke (#83-420-A) FD. TI History for A-4, 765, RTE, shows: 1958, Detroit Edison field notes show FD. STONE recorded LCRC, Liber 3, Page 154, to FOUND STONE (placed railroad spikes around s notes.  Description of corner evidence found and/or method applied in restoring or reestablishing 11/10/95 - G.B. Warnke crew found 3/4" iron pipe being 6.95 feet northwest from s RTE). 2 near witnesses ok to a stone. Stones & bricks are around & under stone. 7-8" in diameter and point on top. Found a 3 inch triangular black area from 21 almost directly under main stone. Set 1" x 36" iron pipe in dark spot and layed and other stones and bricks surrounding iron. 11/28/95 - corner approved by Peer brass renonumentation cap in previously set 1" x 36" iron pipe and witnessed as simple stones are a second	19724 notes corner but not RON PTPE.  1991, G.B. Warnke tone) using Detroit Edison corner:  tone (used as A-4, T6S, Stone was 15" long x to 25 inches deep being main stone on west side Group. 12/7/95 - set hown below.  The position of the corner:  available evidence of long and crossing sign.  The (B-4)  GEORGE B.  WARNAG. IF LAND SURVEYOU NO. 19474