

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A., 1970

For corners in
MONROE (58)
(County)

Located In: Corner Code #

BEDFORD TWP.

T 9 S R 7 E Miscellaneous 7
also known as Post 64 on Michigan - Ohio Line

1. Public Land Survey
2. Property Controlling
in Section
3. Miscellaneous
Property in Sec.
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

1999 Remonumentation Program Corner

I, George B. Warnke, Jr., in a field survey on August, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and / or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- GLO did not set corner.

- 1915 - To Post 64, true bearing N88°29'59" E, Distance 5202.5 feet.

At southwest corner of crossing of north-south road between sections 1 and 2, T9S, R7E, and east-west road thru center of sections 1 and 2; 3 feet east of north-south wire fence and 5 feet north of east-west wire fence; 400.6 feet north of stone quarter corner between sections 1 and 2, T9S R7E, in center line of north-south road, opposite fence west. Stone and stake 20.5 feet east of north-south fence. Post 2217.4 feet south of center of crossroads, approximate corner sections 2, 2 35, and 36. Property east owned by John Striker. Property west owned by M. Benor.

(Latitude 41° 43' 47.09" Longitude 83° 32' 49.84")

To Post 65, true bearing N87°02'32" E., Distance 4484.5 feet

- 9/1995 - G.B. Warnke - notes - Talked to one of the workers at the southwest corner of State Line Road & Telegraph Road about a monument box that was at the southwest corner of the intersection. Worker said that a State of Ohio crew had been at site about a month prior and dug from the middle of the west south bound land of Telegraph Road to west. Found a granite smooth top marker. The person did not see the marker but was told by the Ohio crew that it was the State line marker. The monument box is on the west side of Telegraph Road south of State Line Road. If you stand on monument box looking east, the centerline of State Line Road (on the east side of Telegraph Road) is on line. Also, the monument box is +/- 40 feet north of fire hydrant.

- 6/1999 - MI & OH volunteers - "+" in plate in conc. mon. in mon. box - westerly 75.99' to shiner in pole & westerly 9.69' to old granite stone in mon. box & westerly 76.79' to northeasterly corner of block bldg. @ 6193 southwesterly 63.03' to southeasterly corner of block bldg. @ 6193 & southwesterly 46.40' to shiner in pole southerly 43.51' to "+" on NE bonnet bolt of hyd. & easterly 22.64' to bolt in mon. box

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner is located in Telegraph Road (NE'ly-SW'ly) just south of State Line road (E-W) in west side of asphalt pavement. Granite post was set in 1915 on State line survey by Sherman. Michigan - Ohio state line survey found base of original post now 9.7 feet west of original position. Using G.P.S. and total station, the position of post 64 was agreed on earlier in 1999. On June 16, 1999 with cooperation of surveyors from Lucas County, Ohio Engineers office, Dean Ringle, State Line Chairman & myself, a hole was dug 4 to 5 feet deep. The bottom 3 feet was a 18" diameter x 36" PVC filled with concrete then 6" concrete filled PVC pipe with aluminum plate, marked Post 64 set +/- 6" below surface in a square monument box. The 6 surveyors that agreed upon the final position were: Ralph Williams, Dennis Pritscher, Mike Bartolo, Pat Leonhardt, Dean Ringle & myself - George Warnke. On June 21, 1999, this corner was witnessed by Lucas County Engineers Surveyors with me attending. On August 19, 1999, I rechecked witnesses as below

RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 10/12/1999, COUNTY REP. [Signature]

Corner is accepted as a careful and faithful reestablishment of the position of the original corner as set on 1915 survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

The bottom 3 feet was a 18" diameter x 36" PVC filled with concrete then 6" concrete filled PVC pipe with aluminum plate, marked Post 64 set +/- 6" below surface in a square monument box. Witnesses:

West 76.57 feet to set nail & remon disc in north face of electric pole
South 88° West 76.81 feet to northeast corner of block building @ 6193 Telegraph
South 65° West 63.03 feet to southeast corner of block building @ 6193 Telegraph
East 22.64 feet to I. bolt in monument box on state line @ centerline of Telegraph
South 25° West 43.51 feet to "+" cut in northeast bonnet bolt on hydrant
South 30° West 46.42 feet to found nail & shiner in northeast face of electric pole
West 9.69 feet to base of original post base in a monument box
North 18 feet to centerline of pavement of State Line Road to west

SURVEY &
REMONUMENTATION

MAR 09 2000

SECTION

Signed by [Signature]
Surveyor's Michigan License No. 19474

Date October 28, 1999



FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1994