

DEC 19 2000

MONTCALM COUNTY REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Montcalm  
(County)

Located In:

Bloomer Township

Corner Code #

1. Public Land Survey Sec.8, 9 T. 09 NR. 05 W E-04  
T. R.  
T. R.  
T. R.  
T. R.  
2. Property Controlling S. T. R.  
in Section S. T. R.  
3. Miscellaneous S. T. R.  
Property in Sec. S. T. R.

4. Lot No. Recorded Plat  
5. Private Claims

I, William G. Tingley, in a field survey on June 8, 2000 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1. September 22, 1831, Orange Risdon, Deputy Surveyor, GLO notes, North between sections 8 and 9.

Set quarter section post at 40.00 chains (2640 feet)

Sugar 12" N81°W 13 links (8.58 feet)  
Beech 8" S81°E 20 links (13.20 feet)

2. April 15 1908, John Daoust, County Surveyor, Record of Minutes of Survey

Relocated on CL of R.R. and on st. line bet. Adjacent section corners. Drove bolt in plank. Also drove gaspipe.

Cedar 7" N21 1/4°E 62 feet

3. September 22, 1973, George M. Stevenson, # 13600, Certificate of Survey

E 1/4 cor. section 8 T 9 N R 5 W Found

No witnesses given.

4. October 29, 1973, George M. Stevenson, # 13600, LCRC Liber 1 Page 119

Find R.R. spike on center of R.R. tracks

P.P. NW 71.15 feet  
NE cor brick building SW 64.95 feet  
NW cor Hotel SE 84.75 feet

5. May 5, 1978, Jerry L. Jones, # 19838, Certificate of Survey, Liber 510 Page 1043

E 1/4 corner section 8 T 9 N R 5 W P.K. nail

No witnesses given.

6. December 20, 1990, William G. Tingley, # 30104, LCRC Liber 2 Page 341

Reset corner from old witnesses with I&C

P.P. N45°E 57.25 feet  
P.P. N45°W 71.20 feet  
NE cor brick building S45°W 65.00 feet  
P.P. S45°E 61.11 feet

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Searched the apparent location of the original corner, excavated 3 feet x 6 feet x 2.5 feet deep. Found Iron and cap at road surface and found R.R. spike 6" below surface in old R.R. bed

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set remonumentation pipe in place of Iron and cap in a monument box.


Find N/T E/S P.P. N23°E 58.39 feet  
Find N/T E/S P.P. N30°W 75.65 feet  
Find N/T E/S P.P. S12°E 60.88 feet  
St. sign post N58°W 38.46 feet  
Old foundation brick bldg S45°W 65.00 feet  
NW corner house # 7517 S15°E 85.01 feet

This corner is accepted as the best available evidence of the position of the original corner.

Bearings given are magnetic. Standard remonumentation pipe consists of a Berntsen stainless steel 2 3/8" x 30" pipe with a brass cap stamped "MONTCALM COUNTY REMONUMENTATION, P.S. # 30104"

Signed by William G. Tingley Date 10/11/00

Surveyor's Michigan License No. 30104



Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5		4		3		2		1			
3													
4	7	8		9		10		11		12			
5													
6	18	17		16		15		14		13			
7													
8	19	20		21		22		23		24			
9													
10	30	29		28		27		26		25			
11													
12	31	32		33		34		35		36			
13													

ACCEPTED BY THE MONTCALM COUNTY SURVEY PEEF GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD 10/11/00

William Tingley, PS, Chairman



LIBER 4

PAGE 285



(Continued from front)

## 7. April 17, 1992, William G. Tingley, # 30104, Certificate of Survey

End P.K. nail

P.P.	N45°E	57.25 feet
P.P.	N45°W	71.20 feet
NE cor brick building	S45°W	65.00 feet
P.P.	S45°E	61.11 feet

## 8. April 26, 1995, William G. Tingley, # 30104, Certificate of Survey

Set I&amp;C #30104

N/T E/S P.P.	N30°W	75.40 feet
N/T E/S P.P.	N20°E	58.10 feet
N/T E/S P.P.	S25°E	61.05 feet
NE cor brick building	S40°W	65.05 feet

DEC 19 2000

SECTION