SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

MARQUETTE

For corners in

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Corner Code #

Located In:

. MARQUET	TE	COUNTY
MIC		
RECEIVED	FOR	RECORD

200 DEC 18 PM 12: 44

Patricia	A.	Mood.	lem
Patricia REGISTER	0F	DEEDS	O.S.

(County)			WOND CHOIL DECOS PS
1. Public Land Survey	T <u>47N</u> R <u>27W</u> TR TR	D-5	·
Property Controlling in Section Miscellaneous Property in Sec.	S T R S T R S T R R		LIBER ${f R}2$ PAGE 25
	orded Plat		
5. Private Claims			ABCDEFGHIJK
hereby state that under requirementioned in lines 1 and 2 ab required in the current manual of Bureau of Land Management (mentioned in lines 3, 4 and 5 a	, in a field survey on May rements of P.A. 74, Michigan P.A. ove were in conformance with regular f survey instructions of the United State or by a decree of a Court of Law bove were in conformance with the ee of a Court of Law; established, selow:	of 1970, the corner points lations and rules therefore as stes Department of the Interior, and/or that the corner points rules of the Michigan Board of	2 6 5 4 3 2 3 4 7 8 9 10 11 5 6 18 17 16 15 14 7 8 19 20 21 22 23 9
NOTE: Not more than 2 co on this certificate.	orners, all in the same town and ra	ange, may be recorded	10 30 29 28 27 26
D-5: Quarter Corner Common	ıbdivision survey notes describe t	•	12 31 32 33 34 35 13 RATIFIED BY PEER GROUP P.A. 345 OF 1990 Canny Bussene
1892: Cummings notes page	218 show the corner and indicat	e that it was established	DATE 11/27/00
equidistant and on line between	een the Southwest and Southeast	corners of Section 8. Distant	ce West 2680.4', distance East 2680.4'.
1962: Marquette County Ros of Section 8 to be on the cer	ad Commission sketch of County nterline of the 66' road right-of-w	Road GK recorded in L. 63, Pa ay.	age 250, indicates the South quarter corne
1978: The corner is shown of	on the plat of Westwood No. 1, so	urveyed by Joseph O. Wasie, (S. #15415.
1978: The quarter corner sho	own on the recorded plat of West	wood No. 2, surveyed by Jose	eph O. Wasie, L.S. #15415.
1978: LCRC recorded in L. 1 4" Jack Pine N20W, 12" Jack Pine S38°50 Part A continued on reverse	36.03' 6" Jack Pil 'W 38.46'		2" rerod witnessed by P.K. Nails in:
D-5: 2000: Found and accep	ner position. The 12" Jack Pine i	rface and painted orange. Ide	g comer: Intified the three Charles F. Clark witnesse PK nail was found on the ground. The oth
D-5: 2000: Replaced the 1/2		long rebar capped with a 3 1/4	the position of the corner: 4" diameter aluminum tablet Marquette and located in a monument box 2.2' Norti

10"

J. Pine

J. Pine

N10E,

N13W,

N38E,

28.65

Signed by Herseld W Corlson
Surveyor's Michigan License No. 24589

S01W,

\$39E,

Green Steel Sign Post w/ Yellow Survey Marker Sign

Distance East is 2682.33' and distance West is 2681.80'.

Corner Search Sheet

63.90'

58.74'

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails,

2000035

J. Pine

J. Pine

T47N-R27W

and stamped B.T. Tags affixed.

Date 12-12-00

36.02' (Clark NBT) 31.47' (Clark NBT)

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1976

OF MICH

GERALD W.

CARLSON

SURVEYOR No. 24589



1986: A Certificate of Survey Recorded in L. 357, Page 799 by Larry J. Bussone, L.S. #25833, indicates the South quarter corner of Section 8. The distance 1341.18' East to the 1/16 corner.

1988: A Certificate of Survey Recorded in L. 364, Page 143 by Larry J. Bussone, L.S. #25833, indicates the North one quarter corner of Section 17. The distance West of 2681.82'.

1997: A Certificate of Survey Recorded in L. 418, Page 156 by Larry J. Bussone, L.S. #25833, indicates the North one quarter corner of Section 17. The distance East of 2683.43'.

SURVEY & REMONUMENTATION

FEB 21 2001

SECTION