

SURVEY &  
REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

MARQUETTE COUNTY  
MICHIGAN  
RECEIVED FOR RECORD

200 DEC 18 PM 12:44

For corners in

MARQUETTE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 47N R 27W

I-5

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

*Patricia D. Morley*  
REGISTER OF DEEDS *PM*

LIBER **R2** PAGE **265**

Register of Deeds Stamp & File Number

I, GERALD W. CARLSON, in a field survey on July 14 TH, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-5: Corner common to Sections 10, 11, 14, & 15.

1848: John Burt's original Subdivision survey notes describe the corner monument as a post referenced by:

12" Cedar S55W, 5 links 16" Maple N40E, 16 links

1878: George P. Cummings established corner from Bearing Trees as noted on page 231.

1888: George P. Cummings notes record the following distances: page 225, West 2662.20'; page 231, South 2551.72'.

1891: Cummings Survey Section 10 recorded on page 224 indicates the Southeast corner of Section 10. Distance West 2761.6'. Distance North 2573'.

1891: Cummings Survey of Section 15 shows the Northeast corner. Distance West 2760.6'.

1891: Charles Cummings notes record the following distances: page 225, North 2573.00'; Map page 230, West 2760.6'.

1892: Cummings Survey of Section 11 shows the Southwest corner. Distance East 2683.64'.

1892: Charles Cummings notes record the following distance: Map page 226, East 2683.64'.

No Date: CCI Coordinate Lists for Section 10 indicates South 10275.14 and West 15456.40.

Part A continued on reverse side:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-5: 2000: No original corner evidence found. Found and accepted a 1 1/2" diameter pointed rod 1.5' above ground and drilled into rock, this is a probable Cummings monument. Referenced by a 14" Red Pine (Norway Pine) N64E, 16.45'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-5: 2000: Monument is 1.5' above ground and has been shaped in order to accept a Marquette County Remonumentation Aluminum Cap, stamped to identify the corner. Referenced by:

22" Twin J. Pine N06W, 45.24'

14"

R. Pine

N64E,

16.45' (Clark NBT)

4" Twin Maple S28E, 16.24'

4"

Maple

S65W,

7.48'

Green Steel Sign Post w/ Yellow Survey Marker Sign N07W, 1.75'

Distance North 2575.06', distance East 2686.97', distance West 2766.50'.

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tag attached

T47N-R27W Corner Search Sheet 2000035

Signed by

*Gerald W. Carlson*

Date

12-12-00

Surveyor's Michigan License No.

24589

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995


	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	13		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

RATIFIED BY PEER GROUP  
P.A. 345 OF 1990

*Larry J. Buusma*

DATE

11/27/00



Part A Continued:

9c #437

No Date: CCI Coordinate Lists for Section 11 indicates South 10274.19 and West 10457.23.

1981: A Land Corner Recordation Certificate recorded in L. 4 RC, page 83 by Charles F. Clark, L.S. #25836 indicates a 1-1/2" pointed iron rod in rock outcrop (cliff) witnessed by 16d nails in:

6"	Poplar	N80W,	26.59'	6"	W. Birch North,	18.91'
10"	Norway Pine	N60E,	16.46'	6"	Poplar S10E,	22.44'

No Date: ECI Traverse Sketch Section 10 indicates the Southeast corner with a distance West 2766.49'.

1981: ECI calculation sketch show the distance West to be 2766.49' compared to CCI distance of 2766.06'.

**SURVEY &  
REMONUMENTATION**

**FEB 21 2001**

**SECTION**