

FEB 21 2001

SECTION

**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

MARQUETTE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 48N R 26W

D-1

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, GERALD W. CARLSON, in a field survey on November 10th, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-1: North Quarter Corner of Section 5, T48N-R26W.

Corner not established during Original GLO survey.

No subsequent records recovered

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-1: 2000: SCA survey crews conducted a thorough search of the area and found no evidence of monumentation. Corner position was established equidistant between the NW and NE corners of Section 5 and on line between the SW and S 1/4 corners of Section 32, T49N-R26W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-1: 1996: Set a 2 3/8" O.D. aluminum pipe capped with a 3 1/4" diameter aluminum tablet Marquette County Survey Monument stamped to identify the corner. Monument is 0.15' above ground and on the Easterly slope of a ridge. Referenced by:

16" Maple N85W, 25.48' 15" Maple N37E, 25.24'

14" Maple S76E, 17.57' 7" Maple S32E, 40.18'

South 1/4 corner Section 32, T49N-R26W N89°55'04"E, 3.54'

Green Steel Sign Post w/ Yellow Survey Marker Sign S06E, 3.06'

Distance East 2648.54', distance West 2648.54'

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tags affixed.

Bk. 15, Pg. 73 T48N-R26W Corner Search Sheet 2000035

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD

2000 DEC 22 AM 10:18

Patricia A. Monley
REGISTER OF DEEDS

R2 PAGE 285
Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L
1											
2	6	5	4	3	2	1					
3											
4	7	8	9	10	11	12					
5											
6	18	17	16	15	14	13					
7											
8	19	20	21	22	23	24					
9											
10	30	29	28	27	26	25					
11											
12	31	32	33	34	35	36					
13											

RATIFIED BY PEER GROUP

P.A. 345 OF 1990

Larry J. Burrows
DATE 11/6/00



Signed by Gerald W. Carlson

Date 12-19-00

Surveyor's Michigan License No. 24589