

SURVEY & REMONUMENTATION

FEB 21 2001

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

REC'D FEB 12 PM 2:28

For corners in

Marquette (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>51N</u> R <u>29W</u>	<u>A-7</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____	_____
	S _____ T _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____	_____
	S _____ T _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Patricia M. Manley
REGISTER OF DEEDS

LIBER **R2** PAGE **242**

Register of Deeds Stamp & File Number

I, Gerald W. Carlson, in a field survey on April 19, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
A-7 : NW Corner of Section 19. 1845 : Austin Burt's original township line survey notes describe the corner monument as a post referenced by: 16" Sugar, S55W, 46 l.
8" Aspen, N51W, 33 l.

1846 : William Ives's original subdivision notes added the following two references:
8" Aspen, S87E, 69 l.
8" Aspen, N31E, 17 l.

1940 : Norm Thompson , RLS No. 4348 indicates the Sugar 16 , S55W, 46 l. as "OK, 20"

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

2000 : Found an old 4" square wood post and 3' long X 3/4" diameter pipe, both painted blue and surrounded by stones. Also found remains of stump of original Sugar 16, S55W, 46 l. Distance and bearing check from old wood post to stump. Blue paint lines N-S & E-W from corner. Also found a Ford location tag (1954) and a generic location tag (1982) signed by many area foresters.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2000 : Replaced the old wood post with a 2 1/2" diameter aluminum pipe capped with a 3 1/4" diameter aluminum tablet Marquette County Survey Monument stamped to identify the corner referenced by 16d double head nails in:
10" Yellow Birch, S75E, 14.36' with Ford tag & old blaze
8" Maple S18E, 18.36' with generic tag & old blaze
9" Maple S63W, 39.57'
12" Maple N77W, 33.90'
6' green steel fence post with sign, North, 2.6'
Monument projects 0.40' and is surrounded with large stones
1' diameter and less which surrounded the old wood post.

Note: Bearing trees have painted face, butt and side nail blazes and engraved B.T. tags affixed.

Signed by Gerald W. Carlson Date 8-21-00
Surveyor's Michigan License No. 24589

RATIFIED BY PEER GROUP

P.A. 345 OF 1990

Gerald W. Carlson
DATE 11/6/00

