

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Menominee
(County)

Located In:

Corner Code 77

- | | | |
|------------------------------------|---|------------------|
| 1. Public Land Survey | T <u>34N</u> R <u>26W</u> | <u>G-6, H-7.</u> |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| | T <u> </u> R <u> </u> | |
| 2. Property Controlling in Section | S <u>15</u> T <u>34N</u> R <u>26W</u> | <u>2.</u> |
| | S <u> </u> T <u> </u> R <u> </u> | |
| 3. Miscellaneous Property in Sec. | S <u> </u> T <u> </u> R <u> </u> | |
| | S <u> </u> T <u> </u> R <u> </u> | |

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, David Babbitt, in a field survey on 6/18/86, 19 , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

2. East 1/16 cor. on north section line of Section 15. Not prev. established.

G-6. Wood post. Beech 15, S89W, 46 Lks. W 1/4 corner of Section 15.
 Sugar 12, S41E, 15 Lks.

H-7. South 1/4 corner of Section 15. Wood post. Hemlock 14, N72E, 07 Lks.
 Do 16, S17W, 07 Lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

2. Set MPOL between the N1/4 corner and the NE section corner of Section 15.

G-6. Set in line with old fences north and east and in line with \oint of road west and south.

H-7. Set DNR monument in line with very old fence south and in \oint of E-W road.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2. 1" pipe, 32" long.	5" cedar S11E, 35.75'	G-6. DNR Monument { Nail & brass tag inside of { 20" h.maple, N49W, 24.15' 9" h.maple, S78E, 30.6' 7" h.maple, S45E, 35.6' Power pole N67W, 67.4'
	4" cedar S45W, 40.25'	
	5" cedar N72W, 63.10'	
	5" cedar N13W, 29.47'	

H-7. DNR Monument.
 Nail & brass tag inside of Apple tree S35W, 24.2'
 Powerpole S7E, 28.7'
 5" r.pine, N57E, 61.0'
 10" cedar, N48W, 58.7'

Signed by

David B. Babbitt

Date

9-11-86

Surveyor's Michigan License No.

21558