

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Menominee</u> <small>(County)</small>	Located In:	Corner Code ##	
1. Public Land Survey	T <u>35N</u> R <u>25W</u>	<u>K-8.</u>	
	T _____ R _____	_____	
	T _____ R _____	_____	
	T _____ R _____	_____	
2. Property Controlling In Section	S _____ T _____ R _____	_____	
	S _____ T _____ R _____	_____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____	
	S _____ T _____ R _____	_____	

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, David Babbitt, in a field survey on 3/31, 19 86,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

K-8. East 1/4 corner of Section 23. Mich. Conservation Dept. Conc. Mon. with brass cap
stamped GA Shadko. Part of public access site survey 55-1, surveyed in 1943.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-8. Found monument as shown on a survey drawing of State public fishing site (55-1) by G.A.
Shadko surveyed in 1943. This monument has been accepted and used by several other
land surveyors in the past but is not of record under Act 74 of 1970.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-8. 4" Brass Cap Encased in Concrete.
(Public Fishing Site Mon.)
22" w.ash S60E, 340.6'
7" apple S60W, 55.8'
D.N.R. Mon. in Conc. Public Fishing
Site. N85W, 74.9'
4" Balm of Gilead N21W, 195.6'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by David B. Babbitt Date 8-1-88

Surveyor's Michigan License No. 21558