LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in						
Menominee (County)	Located In:	Corner Code #				
Public Land Survey	T 36N R 28W	F08	*			
!. Property Controlling n Section	T R S T R S 21 T 36N R 28W S T R	05				
3. Miscellaneous Property in Sec.	S T R R R		Register of Deeds Stamp	& File Number		
1. Lot No. Rec	orded Plat			H I J K L M		
bove were in conformance with renstructions of the United States D. Court of Law and /or that the cohe rules of the Michigan Board e-established, monumented, recover NOTE: Not more than 2 corners in this certificate.	74, Michigan P.A. of 1970, the corner posegulations and rules therefore as required epartment of the interior, Bureau of Larborner points mentioned in lines 3, 4 and 5 of Land Surveyors or by a Decree	do hereby state oints mentioned in lines 1 and 2 d in the current manual of survey and Management or by a decree of 5 above were in conformance with of a Court of Law; established, may be recorded	5 6 18 17 16 7	3 - 2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
(F08) Center One-Quarter Corner of Section 21. Not set in original survey, no evidence of subsequent establishment.						
(05) Center-North One-Sixteenth corner of Section 21. Not set in original survey, no evidence of subsequent establishment.						

- 3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (FO8) Corner position established at the intersection of the North-South and East-West One-Quarter lines of Section 21.
- (05) Corner position established mid-point and on-line between the Center One-Quarter corner and the North One-Quarter corner of Section 21.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(F08)	DNR monument	(05) DNR monument		
13" Maple	N25E 86.86' (1/4S,BT)	5" Maple N26E 36.55' (1/16S,BT)		
10" Maple	N80E 66.28' (1/4S,BT)	10" Maple N89E 32.86' (1/16S,BT)		
10" Maple	S45E 82.18' (1/4S,BT)	7" Oak S33E 40.62' (1/16S,BT)		
6" Oak	S28E 79.02' (1/4S,BT)	6" Oak S32W 55.42' (1/16S,BT)		
All trees a	are blazed, scribed, and	All trees are blazed, scribed, and		
painted. N	Measurements are to nail in	painted the managements are to nail in		
side of tre	ee, bearings are magnetic.	painted propents are to nail in side of tree, bearings are magnetic.		

Surveyor's Michigan License No.

For the Michigan Department of Natural Resource

50447

erems con

SURVEYOR

FORM MAROVED BY MIN

AN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 Revised May 14, 1975

July 9, 2014

Revised Jan., 1983 Rervised Oct., 1995

20310

20309