

DEC 27 1993

904

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 283 PAGE 430

For corners in

Missaukee
(County)

Located In:

Corner Code #

1. Public Land Survey

T 21N R 8W

K-13

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

MISSAUKEE COUNTY MICHIGAN

RECORDED DEC 16 1993 12:40 P.M.

Reslyn Flare
REGISTER

Register of Deeds Stamp & File Number

I, J. Dean Geers, in a field survey on December 13, 19 93,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-13) 1837 GLO Section post by John Brink, Deputy Surveyor
Sugar 12 N 16 1/2° E 36, Sugar 11 N 51° W 43

K-13) 1977 McClung L.C.R.C., Liber 1, page 567, Set 3/4" rod and cap, Power pole N 15° E
74.1', Tele box S 20° E 37.75'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-13) Section corner common to Sections 35 and 36

Found 3/4" Iron ±3' easterly of centerline of road Northerly and ±1' Northerly of centerline
of road East-West. This corner is accepted as a careful and faithful reestablishment of the
position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-13) Replaced found 3/4" Iron with 1/2" x 36" Iron and Missaukee County monument in monument
box

N 21° E - 74.10 - Power pole
N 31° E - 47.72 - Top of center of telephone riser
S 25° E - 37.72 - Top of center of telephone riser
S 46° W - 43.41 - Set 1/2" Iron and cap

Peer Group Reviewed and Approved

Date: 12-15-93

J. Dean Geers
J. Dean Geers, Missaukee Co. Representative

Signed by

Date 12/15/93

Surveyor's Michigan License No. 33977