

SURVEY &
REMONUMENTATION

MAY 28 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

#1104

For corners in

LIBER 308 PAGE 897

Missaukee County (County) Located In: Corner Code #

1. Public Land Survey T 22N R 7W D-13
T R
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

MISSAUKEE COUNTY MICHIGAN

RECORDED DEC 30 1996 43

Carolyn Klorer
Register of Deeds Stamp Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Daniel E. Schripsema, in a field survey on October 1, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate

A. Description of original monument and accessories and/or subsequent restoration:

D-13) 1837 GLO survey by John Brink, Deputy Surveyor - set Quarter Section post - beech 10" N18 1/2 E 26, beech 10" N72W 46
1899 survey of Sec. 5 T21N, R7W, county surveyor field notes, w. pine stub 30" N10W 24, w. pine s. 13" S40E 64
1989 Daniel E. Schripsema LCRC No. 786, set 1/2" iron / cap by Single proration per survey of record dated 3/1989, and on line corners E & W, 4" x 6" grd. RI. Post S15W 84.11', 12" maple N30E 59.20', 14" w. pine N60E 48.93', 18" w. pine S10E 55.73'
1989 Daniel E. Schripsema survey, liber S2, pg. 466-468
1991 Daniel E. Schripsema survey, liber S3, pg. 61

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-13) Quarter corner common to Section 32, T22N, R7W and Section 5, T21N, R7W, Found 1/2" iron / cap per record. This corners accepted as a careful and faithful re-establishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-13) Set Missaukee County Remonumentation. Cap on existing iron
10" White pine S36W 60.66'
12" maple N30E 59.20'
14" w. pine N60E 48.93'
18" w. pine S30E 55.73'

Peer Group Reviewed and Approved

Date: 12-30-96
J. Dean Geers, Missaukee Co. Representative

Signed by: Daniel E. Schripsema

Date: 12-30-96

Surveyor's Michigan License No. 24617

