

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Missaukee County
(County)

Located In:

Corner Code #

1. Public Land Survey

T 22N R 7W

M-2

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Daniel E. Schripsema, in a field survey on October 1, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate

A. Description of original monument and accessories and/or subsequent restoration:

- M-2) 1938 GLO set quarter post section 1; Maple 11 S33W 22, Hemlock 10 N58W 10
1900 Beuthien survey of Sec. 6, 22-6; FB #34, pg. 56, county surveyor notes; CF Post S87E 49
1996 Daniel E. Schripsema survey, liber S-3, pg. 383; Set 1/2" iron and cap
S69E 14.52' 12" twin maple, S45W 39.23 7" Maple, N46W 33.54 14" twin maple, N10E 65.85 12" twin oak

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- M-2) Corner common to Section 1, T22N, R7W and Section 6, T22N, R6W. Found 1/2" rerod/cap of record which was set in the middle of trail road, 3.5' S. & 25.2' E of fence corner to the West and 3.5' N. & 25.2' W of fence corner to the East.

This corner is accepted as a careful and faithful reestablishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- M-2) Set Missaukee County Monument on existing iron.

S69E 14.52' 12" twin Maple
S45W 39.23' 7" Maple
N46W 33.54' 14" twin Maple
N10E 65.85' 12" twin Oak

Peer Group Reviewed and Approved

Date: 12/23/97


J. Dean Geers, Missaukee Co. Representative

Signed by

Surveyor's Michigan License No.

24617

Date 12-2-97



SURVEY &
REMONUMENTATION

JAN 16 1998

SECTION

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1997
REVISED MAY 14, 1997
REVISED JAN., 1998
REVISED OCT., 1998