		uirement of Act 74, Mich.	P.A. 1970
For corners in	· ·		# 1337
Missaukee County (County)	Located in:	Corner Code #	LIBER 3/5 PAGE //30
1. Public Land Survey	T 22N R 7W	<u>M-10</u>	MISSAUKEE COUNTY MICHIG
	TR TR		/a
	TR		RECORDED DEC 2 9 1997
2. Property Controlling in Section	S TR S TR		
3. Miscellaneous	S TR		Carolyn Flor
Property in Sec.	S TR	*******	Register of Deeds Stamp & Fil Number
4. Lot No. Recorde	d Plat		
4. Lot No, Recorded Plat			ABCDEFGHI _{JK} 1
· ·			
			3
I, <u>Daniel E, Schripsema</u> , in a field survey on <u>October 1</u> , 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in			4 7 8 9 10 11
lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in			5
			6 18 17 16 15 14
lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered,			7
found as expressed below:	•	,,	$\frac{8}{1}$ $\frac{1}{5}$ $\frac{2}{1}$ $\frac{2}$
NOTE: Not more than 2 corners, all in the same town and range, may be recorded			
on this certificate			1
	•		12 31 32 33 34 35 3
			13
	,	·	
A. Description of original mon	ment and accessories and	d/or subsequent restoration:	
1916 Beuthien surve 1930 Beuthien surve 1978 Jerry L. Wilco	ey; FB #9, pg. , county sur ey, FB #34, pg. 68, county x LCRC, #531; set ½" iron	Balsam 7 N42W 14, Elm 10 veyor notes; Cedar stake, Elm surveyor notes; Cedar Stake, I & cap Abut 159.56, S23W 16" R. P	8 S40E 80 Elm 9 S45E 52.8'
B. Description of corner evide	nce found and/or method a	applied in restoring or reestablis	shing corner:
M-10) Corner common to Section 25, T22N, R7W, and Section 30, T22N, R6W. Found ½" rerod and cap of record.			
C. Description of monument for	corner and accessories e	stablished to perpetuate locating	the position of the corner
M-10) Set Missaukee Corr			g the position of the outles
	orner bridge abutment		·
S18W 126.29' 1	6" Red Pine		Page Group Davigued and Annual L
	S67W 43.57' 8' red pine S34W 69.71' 9' red pine		Peer Group Reviewed and Approved
S28E 107.43' 5" elm			
			J Deam Geers, Missaukee Co. Representative
\bigcirc .	01		
Signed by Share Share			12-2-81
Surveyor's Michigan License No	24617	Date	
DANIEL E	(*)		
SCHRIPSENA	128		
LAND SURVEYOR		VEY & FORM APPROVED BY	MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28,
No.	REMONU	MENTATION	REVISED MAY 14,

SECTION

JAN 1 6 1998