

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
WISBAUKEE  
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 23N R 6W

1-7, 1-9

T R

1-10, 1-11

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL F. ROSER, in a field survey on SEPTEMBER 13, 19 90,  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1-7

1-9

1-10

1-11

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1-7

1-9

1-10

1-11

REESTABLISHED BE COR SEC 15  
MIDWAY BETWEEN 1/8 LINE FN'S  
TO WEST, 1/4 MILE N & S, AND  
IN CTR N-S GRAVEL ROAD. THIS  
IS IN LINE W/OLD FENCE LINE  
REMAINS TO EAST.

FD 1/2" IRON W/BATTERED RLS  
CAP FOR NE COR SEC 27;  
PROBABLY BY L.S., J. MILCOX  
#14102. OLD BARB-WIRE FN TO  
E IS 6' ± 2' N. OLD FN WEST  
IS 28' S. N-S ROW FN'S 32' ±  
E & 33' ± W. CTR OF N-S GRAVEL  
RD IS 2'E.

FD 1/2" IRON W/ BATTERED RLS  
CAP FOR E 1/4 COR SEC 27. COR  
IS IN CTR N-S GRAVEL RD & IN  
LINE W/NEWER STEEL FN POST FN  
TO EAST. FN REMAINS N'LY ARE  
30' ± 3' N. OLD N-S ROW FENCE  
IS 33' ± 3' WEST & OLD ROW FN  
NORTH IS 32' ± E.

FD 1/2" IRON ROD; FITS 3 LS,  
J. MILCOX WITS FOR SE COR  
SEC 27. COR IS 2 1/2' E OF  
INTER B.TOP RD S & GRAVEL RDS  
N & E. N-S ROW FN IS 35' W.  
ROW FN N IS 32' E. ROW FN S  
IS 36'E AND ROW FN'S TO E ARE  
35' N & 34' S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1-7

1-9

1-10

1-11

DROVE 5/8" X 3/4" REROD W/RLS  
CAP.  
3" RED PINE N20°W 100.60'  
16" MAPLE S35°E 107.40'  
3" W PINE S20°E 103.59'  
CTR N END 18'  
CHP N35°W 37.40'  
SET CED POST EAST 33'

FD 1/2" X 10" IRON ROD W/RLS  
CAP.  
5" W PINE N70°E 63.36'  
4" W PINE S85°E 48.49'  
POWER POLE S30°E 61.63'  
FD 1/2" IRON ROD W/RLS  
CAP #14102 EAST 33.02'

FD 1/2" IRON ROD W/RLS CAP.  
7" TRPL MAPLE N75°W 63.46'  
4" MAPLE N65°W 59.82'  
FACE 4" X 4.5" TALL STEEL  
PIPE IN CONC EAST 29.1'  
5" MAPLE S65°W 35.68'

FD 1/2" IRON ROD W/RLS CAP.  
6" R PINE N60°W 55.15'  
FN-GATE POST N35°E 59.03'  
GUARD POST BY 4" X 4"  
TELE CO BOX S50°E 51.23'  
POWER POLE S55°W 38.47'

\*WIT BY OTHERS.

Signed by Carl F. Roser 8/13/92 Date

Surveyor's Michigan License No. 12028

