Land Corner Recordation Certificate

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Craig W. McVean						Field Survey Date: Aug. 22, 2017								
For corner(s) in: Missaukee					County									
Origi	inal Public L	and Survey	Corner Code											
S		т		R										
S		T		R				В	CDI	E F (G H	l J l	K L I	VI ₁
S	3/	Т		R			1		20 0			1		71
S		T		R			2	- 6	-5-	4	- 3	2	1	2
	2					-	3	- i -	1000		- i -		- i-	3
Property Controlling Corner						Corner Code	4	7	8	9-	10	-11	12	4
S		,,		R			- 5	- 1	- 21					5
S		T		R				40	47	40	10			-
S		Т		R			6	18	17	16	15	14	13	6
S		Т		R			7		-				-	7
							8	19	20	21	22	23	24	8
Property Corner						Corner Code	9	i	- 1		-			9
S	22	Т	23N	R	7W	12	10	30	29	28	27	26	25	10
S	-	т		R			11				7		20	
S		Т		R										11
s		т		R		315039	12	31	- 32	- 33	- 34	35	36	12
				-			13 A	В (C D I	E F (G H	1 1 1	< L N	J 13
Protracted Public Land Survey Corner						Corner Code	,	(D (י ט כ	_ ' '	3 11	J	\ L I	VI
S	22	Т	23N	R	7W	Н8								
S		Т		R			-							
s		т		R			-							
S		Т		_ R _			•							
							-							

Part A: Corner History

<u>H8</u> – C ¼ Sec. 22, T23N, R7W – None

<u>12</u> – CS 1/16 Corner Sec. 22, T23N, R7W – None

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

H8 - C ¼ Corner Sec. 22, T23N, R7W
Set 2" Alum. Cap on 5/8" x 34" long iron rebar at intersection of ¼ lines per Standard BLM procedure. N-S single strand is 8'± West.

12 - CS 1/16 Corner Sec. 22, T23N, R7W Set 2" Alum. Cap on 5/8" x 34" long iron rebar per Standard BLM procedure. N37°W 51.5' to steel fence post for corner of single strands N & W.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

H8 - C 1/4 Corner Sec. 22, T23N, R7W
Stamped 2" Aluminum Cap on 5/8" x 34" long iron rebar.

S52°W 17.21' to set N & T in SE side 4" W. Pine N47°W 39.67' to set N & T in NW side Triple 13"
Cherry
N11°W 19.94' to set N & T in E. side 5" Fir N88°E 25.13' to set N & T in S. side 4" W. Pine

12 - CS 1/16 Corner Sec. 2, T23N, R7W Stamped 2" Aluminum Cap on 5/8" x 34" long iron rebar. N68°W 22.95' to set N & T in N. side 12" Cherry

N68°W 22.95' to set N & T in N. side 12" Cherry N28°W 55.78' to set N & T in W. side 16" W. Pine N40°E 20.14' to set N & T in SE side 8" R. Maple S49°E 55.97' to set N & T in SW side 16" R. Maple



Craig W. McVean

Professional Surveyor's License No.: 39088

Prepared By: Craig W. McVean Michigan Dept. of Natural Resources 8015 Mackinaw Trail Cadillac, Michigan 49601