

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Missaukee
(County)
Located In
Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Section

4. Lot No:
Recorded Plat:
5. Private Claims:

I, Craig W. McVean, in a field survey on Aug. 14, 2008 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

6 - None
Z - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

6 - NE 1/16 Corner Section 4 - Set stamped 2" Aluminum cap on 5/8" x 34" rebar per standard BLM procedure. Remains of E-W fence is 5'± S.
Z - N 1/16 corner common to Sections 3 & 4 - Set Stamped 2" Aluminum cap on 5/8" x 34" rebar per standard BLM procedure. Corner falls in centerline of N-S bit. Rd. New horse pasture fence to West is 12'± N.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

6 - Stamped 2" Aluminum cap on 5/8" x 34" rebar.
N27°E 8.84' to set nail & tag in E. side 15' Sugar Maple
N36°W 24.55' to set nail & tag in SW side 7" Sugar Maple
N85°W 25.71' to set nail & tag in N. side 10" Sugar Maple
S19°W 23.20' to set nail & tag in W. side 18" Sugar Maple
Set Blue Carsonite Post with location tag 1' NW
Z - Stamped 2" Aluminum cap on 5/8" x 34" rebar.
West 33.01' to set 2" Aluminum cap on 5/8" x 34" rebar on-line at ROW line with a Blue Carsonite Post and location tag
N51°W 77.86' to set nail & tag in NE side 9" Spruce
N23°W 150.82' to set nail & tag in NE side 7" Spruce
S12°W 164.48' to set nail & tag in W. side 4" x 6" wood guard post and telephone Riser

Signed by: [Signature] Date: 6/1/2010
Surveyor's Michigan License No.: 39088