

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Missaukee
(County)

Located In

Corner Code #

1. Public Land Survey T _____ R _____
T _____ R _____
2. Property Controlling
in Section S 17 T 24N R 7W 5
S 18 T 24N R 7W 12
3. Miscellaneous
Property in Section S _____ T _____ R _____
S _____ T _____ R _____

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on Jan. 24, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

5 - None

12 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

5 - CN 1/16, Cor. Sec. 17.-Set stamped 2" Aluminum cap on 5/8" x 34" rebar per Standard BLM procedure.

12 - CS 1/16, Cor. Sec. 18.-Set stamped 2" Aluminum cap on 5/8" x 34" rebar per Standard BLM procedure. Fence corner for fences S & W is 6'± W and 6'± S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

5 - CN 1/16, Sec. 17
2" Aluminum stamped cap on 5/8" x 34" rebar
N60°E 14.24' to set N & T in S. side 7" W. Pine
S08°W 42.51' to set N & T in E. side 11" Twin Oak
S52°W 11.24' to set N & T in S. side 10" Twin B. Cherry

12 - CS 1/16, Sec. 18.
2" Aluminum stamped cap on 5/8" x 34" rebar
N66°E 14.43' to set N & T in NW side 4" Cherry
S70°E 18.79' to set N & T in N side 2" Oak
S01°E 19.73' to set N & T in W. side 9" Cherry