

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Missaukee

(County)

Located In

Corner Code #

1. Public Land Survey

T 24N R 8W L4  
T 24N R 8W L6

2. Property Controlling  
in Section

S T R  
S T R

3. Miscellaneous  
Property in Section

S T R  
S T R

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Craig W. McVean, in a field survey on April 15, 2004 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L4 - CSR - E.A. Beuthien - 1914

L6 - None

Stake and stone

Hemlock 13" N62½°E 29 L.

Maple 36" N33°W 40 L.



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

L4 - Center ¼ Cor. Sec. 12 - No conclusive evidence of Beuthien position found. Set 2" Alum. Cap on 5/8" x 34" iron rebar at intersection of ¼ lines. Found old down E-W barb wire fence is 4± S.

L6 - C ¼, Sec. 13 - Set 2" Alum. Cap on 5/8" x 34" iron rebar at intersection of ¼ lines.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L4 - Stamped 2" Alum. Cap on 5/8" x 34" rebar  
N34°W 23.78' to set N & T in NW side 10" R. Maple  
N20°E 30.63' to set N & T in NW side 5" R. Maple  
N75°E 30.33' to set N & T in N side Tw. 29" Oak  
S28°E 2.98' to set N & T in E side 8" R. Maple  
Set blue carsonite post w/ loc. tag 0.8' N.

L6 - Stamped 2" Alum. Cap on 5/8" x 34" rebar  
N65°W 10.79' to set N & T in NE side 15" R. Maple  
N35°E 18.43' to set N & T in E. side 9" Cedar  
S58°W 45.55' to set N & T in N. side 18" R. Maple  
S10°W 30.42' to set N & T in E. side 16" Cedar  
Set blue carsonite post w/ loc. tag 1' NNE

Signed by:

*Craig W. McVean*

Date:

*5/20/2004*

Surveyor's Michigan License No.:

39088